

Digital Television Broadcasting Systems Testing in Brazil

Kiev, Ukraine - 13-15 November 2000

Interregional Seminar on the Transition from SECAM to Digital TV Broadcasting

Renato Maroja - maroja @cpqd.com.br Fundação CPqD - www.cpqd.com.br Campinas - SP - Brazil



Organization of the tests

- Entities and roles
 - ANATEL National Agency of Telecommunications Brazilian regulating authority
 - Conducts the process of defining a DTV standard for Brazil
 - Authorized (after a public consultation) the realization of the field tests
 - Contracted CPqD as consultant in the process
 - Will define the DTV standard based on the tests results and other technical and non-technical aspects
 - SET (Brazilian) Society of Television Engineering
 - ABERT Brazilian Association of Radio and Television Broadcasters
 - SET/ABERT studies the evolution of DTV standards since 1994, and has structured task groups to carry on the tests
 - Makes planning studies to consider digital channels along with analog channels
 - Technological agreement with Instituto Mackenzie Human resources
 - Instituto Mackenzie a Brazilian private University, in São Paulo
 - Tests methodologies
 - Acquired test equipment, set up the laboratory and field tests installations
 - Executed the tests and reported the results to ANATEL, together with SET/ABERT



Organization of the tests

- Entities and roles (cont)
 - CPqD Private foundation with expertise in Telecommunications
 - support in systems aspects CPqD works in multiple areas in telecommunications
 - analysis and consolidation of the laboratory tests methodology
 - development of ambiences for systems simulations
 - analysis and consolidation of the field tests methodology
 - checking and support in the laboratory and field tests
 - development of tools for planning studies
 - analysis of the tests results
 - advice on other aspects of the introduction of Digital TV in Brazil



~1100 employees 600 000 m2



Laboratory and Field Tests

- Tests objectives: Compare terrestrial DTV systems with respect to the transmission layer
- Laboratory Tests robustness/capacity analysis of the systems under controlled conditions
 - Interference A to D, D to A, D to D, CW and FM: planning
 - Robustness to impulsive noise
 - Multipath performance
 - static, single and multiple echoes
 - · dynamic, Doppler shift, mobility
 - BER x C/N performance in white noise (AWGN) modulation, planning, transmitter power



Interference: Protection Ratios

D/U = Desired/Undesired Signal power ratio (dB) Lower ratios P more robustness

Digital into Analogue (*)	ATSC	DVB-2K	DVB-8K	ISDB
Co-channel	37	38	38	38
Upper adjacent	-9	-9	<u>-9</u>	-9
Lower adjacent	-7	-7	-7	-11
Analogue into Digital	ATSC	DVB-2K	DVB-8K	ISDB
Co-channel	5	7	7	6
Upper adjacent	-32	-31	-26	-34
Lower adjacent	4 0	-27	-32	-34
Digital into Digital	ATSC	DVB-2K	DVB-8K	ISDB
Co-channel	15	20	20	18
Upper adjacent	-27	-25	-25	-29
Lower adjacent	-27	-25	-24	-24


(*) CCIR 4: 37,5 dB

Taboo channels interference: irrelevant




Robusteness to Impulsive Noise

Digital signal + gated Noise \triangleright C/Neq Gate: 30s cycle, 12,5 Hz to 100 Hz, fixed T_W BER < 3 x 10⁻⁶ within 2 minutes counting






Multipath - single static echo





C/N degradation with single echo

- •Increased echo amplitude requires higher C/N (imposes penalty)
- •DVB-T and ISDB demodulators showed evolution along the tests
- •COFDM: guard interval
- •ATSC cannot stand strong echoes: ~2 dB with high penalties
- •8VSB: (long, complex) transversal equalizers





BER x C/N performance

COFDM: robustness x payload


 $C/N @ BER = 3 \times 10^{-6}$

•ATSC Zenith: 14.5 dB

•DVB-T chip M 2/3 1/32 8K: 16.9 dB @ LOP

•DVB-T NDS 3/4 1/8 2K: 18.8 dB

•ISDB-T DiBEG 3/4 1/16 2K/4K/8K: 18.5 dB





Field Tests

- Field tests robustness/capacity analysis under real reception conditions
 - Coverage real world reception includes white noise, multipath, interference from other channels and impulsive noise
 - Gap filler recover coverage on a shadowed spot
 - Indoor reception high attenuation and time varying multipath
 - Mobility Doppler frequency shift some trajects in São Paulo, near the transmitter



Field Tests - TX Site

São Paulo

- Biggest market in Brazil: 40% GNP
- Economical potential
- "Acid test": difficult coverage
 - Topographic conditions gap filler
 - High density of buildings in some regions
- UHF channel 34 (593 Hz center frequency)



Source: SET/ABERT Final Report - Part 2 Public Consultation 237 - June 02, 2000

TX station

- Site definition for TV Cultura tower: coverage, infrastructure and space for equipments and for antenna in tower
- Transmitter: Harris DCD20PL1, operated at 2,5 KW for all systems
- Antenna: 104 m agl; 9.3 dBd; 12 KW max. ERP



Field Tests - RX Site

- RX Van
- mast 10 m agl
- Antenna: Scaffner, 2.6 dBd
- Pre-amplifier, hybrids
- Noise Generator
- Receivers availability
- MPEG 3 Decoder
- Spectrum Analyzer





Source: SET/ABERT Final Report - Part 2 Public Consultation 237 - June 02, 2000

Measurement period: Nov 9, 1999 to Abril 28, 2000



RX Test sites in São Paulo



Measurement Procedure

- Point RX antenna to obtain best reception
- •Measure received C/N @ C = -30 dBm
- Add external noise up to BER Threshold or artifacts;
- •Calculate available margin, electric field, etc

C = Signal Power

N = Noise power in channel bandwidth

C/N = Signal to noise ratio


Measured points

- •17 radials 15° apart
- •distances: 3, 6, 9, 12, 15, 20, 25, 30, 40 Km



127 test points: ATSC and DVB-T 2K


Criterion: Margin > 0 dB





127 test points: ATSC and DVB-T 2K


Criterion: Margin > 0 dB






27 test points: ATSC, DVB-T 2K,

Criterion: Margin > 0 dB






Criterion: Margin > 0 dB





Gap filler measurement sites




Out of range



Outdoor Reception - Gap Filler


Improvement of reception with gap filler Antenna is re-oriented with gap filler on/off Distance from main transmitter ~5,6 Km -> ~19 ms





Indoor Reception

12 sites where the 3 systems were tested under identical conditions Indoor antenna: UHF log-periodic - Silver Sensor





SET/ABERT Reports

The data, tables and graphs presented here were extracted mainly from the SET/ABERT Final Report - Part 2, that is available in Portuguese and in English at: www.anatel.gov.br

These results express the conclusions arrived at by SET/ABERT, and do no express ANATEL's viewpoint.

Thank you for your attention