

International Telecommunication Union

**ITU-R**  
Radiocommunication Sector of ITU

**Recommendation ITU-R SA.1159-4**  
(07/2017)

**Performance criteria for data transmission  
systems in the Earth exploration-satellite  
service and meteorological-satellite service**

**SA Series**  
**Space applications and meteorology**

## Foreword

The role of the Radiocommunication Sector is to ensure the rational, equitable, efficient and economical use of the radio-frequency spectrum by all radiocommunication services, including satellite services, and carry out studies without limit of frequency range on the basis of which Recommendations are adopted.

The regulatory and policy functions of the Radiocommunication Sector are performed by World and Regional Radiocommunication Conferences and Radiocommunication Assemblies supported by Study Groups.

## Policy on Intellectual Property Right (IPR)

ITU-R policy on IPR is described in the Common Patent Policy for ITU-T/ITU-R/ISO/IEC referenced in Annex 1 of Resolution ITU-R 1. Forms to be used for the submission of patent statements and licensing declarations by patent holders are available from <http://www.itu.int/ITU-R/go/patents/en> where the Guidelines for Implementation of the Common Patent Policy for ITU-T/ITU-R/ISO/IEC and the ITU-R patent information database can also be found.

### Series of ITU-R Recommendations

(Also available online at <http://www.itu.int/publ/R-REC/en>)

Series	Title
<b>BO</b>	Satellite delivery
<b>BR</b>	Recording for production, archival and play-out; film for television
<b>BS</b>	Broadcasting service (sound)
<b>BT</b>	Broadcasting service (television)
<b>F</b>	Fixed service
<b>M</b>	Mobile, radiodetermination, amateur and related satellite services
<b>P</b>	Radiowave propagation
<b>RA</b>	Radio astronomy
<b>RS</b>	Remote sensing systems
<b>S</b>	Fixed-satellite service
<b>SA</b>	<b>Space applications and meteorology</b>
<b>SF</b>	Frequency sharing and coordination between fixed-satellite and fixed service systems
<b>SM</b>	Spectrum management
<b>SNG</b>	Satellite news gathering
<b>TF</b>	Time signals and frequency standards emissions
<b>V</b>	Vocabulary and related subjects

*Note: This ITU-R Recommendation was approved in English under the procedure detailed in Resolution ITU-R 1.*

Electronic Publication  
Geneva, 2017

© ITU 2017

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without written permission of ITU.

## RECOMMENDATION ITU-R SA.1159-4

**Performance criteria for data transmission systems  
in the Earth exploration-satellite service and meteorological-satellite service**

(Question ITU-R 141/7)

(1995-1997-1999-2006-2017)

**Scope**

This Recommendation specifies the performance objectives for data transmission systems of the Earth exploration-satellite service (EESS) and meteorological-satellite service (MetSat) operating either in low-Earth orbit (LEO) or in geostationary orbit.

**Keywords**

EESS, METSAT, non-GSO satellites, GSO satellites, data transmission, interference criteria

**Related Recommendations and Reports**

Recommendations ITU-R SA.1020, ITU-R SA.1627 and ITU-R SA.1021

The ITU Radiocommunication Assembly,

*considering*

- a)* that the hypothetical reference system specified in Recommendation ITU-R SA.1020 defines space-to-Earth links for data transmission, encompassing direct readout of data acquisition of recorded data, as well as links for data dissemination, and direct data readout, data collection and data collection platform (DCP) interrogation by satellite;
- b)* that performance objectives for these transmissions must be consistent with the attendant functional requirements and with the performance limitations associated with the systems and frequency bands in which the requirements will be fulfilled;
- c)* that performance objectives for representative systems operating in the Earth exploration-satellite service (EESS) and meteorological-satellite service (MetSat) are intended to provide guidelines for the development of actual systems;
- d)* that performance objectives may be determined using the methodology described in Recommendation ITU-R SA.1021;
- e)* that the performance objectives are a prerequisite for the determination of interference criteria;
- f)* that Recommendation ITU-R SA.1627 contains the telecommunication requirements and characteristics of EESS and MetSat systems for data collection and their platform locations,

*recommends*

- 1** that links associated with data transmission systems in the EESS and MetSat using satellites in low-Earth orbit (LEO) should have the performance objectives specified for the frequency bands in Table 1;

2 that links associated with data transmission systems in the EESS and MetSat service using satellites in geostationary orbit should have the performance objectives specified for the frequency bands in Table 2.

TABLE 1  
Performance objectives for links in the EESS and MetSat service  
using LEO satellites

Frequency band	Satellite service	Modulation	Applicable elevation angle (degrees)	Minimum C/N or maximum BER	Percentage of time (%)	Function and type of earth station
137-138 MHz (space-to-Earth)	MetSat	Analogue	$\geq 25$	10 dB	99.9	Direct data readout, low-gain antenna
	MetSat	Digital	$\geq 5$	$10^{-6}$	99.9	Direct data readout, tracking antenna
	MetSat	Digital	$\geq 5$	$10^{-5}$	99.6	CDA station, tracking antenna
400.15-401.00 MHz (space-to-Earth)	MetSat	Digital	$\geq 5$	$10^{-6}$	99.9	Direct data readout, low-gain antenna
401-403 MHz (Earth-to-space)	MetSat and EESS	Digital	$\geq 5$	$10^{-5}$	99.6	Data collection, low-gain antenna
460-470 MHz (space-to-Earth)	MetSat and EESS	Digital	$\geq 5$	$10^{-5}$	99.6	DCP interrogation, low-gain antenna DCP data, tracking antenna
1 670-1 710 MHz (space-to-Earth)	MetSat and EESS	Digital	$\geq 5$	$10^{-3}$	99.99	Direct data readout and recorded data acquisition, low-rate data, tracking antenna
		Digital	$\geq 5$	$10^{-6}$	99.9	
2 200-2 290 MHz (space-to-Earth)	EESS	Digital	$\geq 5$	$10^{-6}$	99.6	DCP data, Tracking antenna

TABLE 1 (end)

Frequency band	Satellite service	Modulation	Applicable elevation angle (degrees)	Minimum C/N or maximum BER	Percentage of time (%)	Function and type of earth station
7 750-7 900 MHz (space-to-Earth)	MetSat	Digital	$\geq 5$	$10^{-3}$	99.99	Recorded data acquisition, high-rate data, tracking antenna
	MetSat	Digital	$\geq 5$	$10^{-6}$	99.9	
8 025-8 400 MHz (space-to-Earth)	EESS	Digital	$\geq 5$	$10^{-3}$	99.99	Direct data readout and recorded data acquisition, tracking antenna
		Digital	$\geq 5$	$10^{-6}$	99.9	Recorded data acquisition, tracking antenna
		Digital	$\geq 5$	$10^{-5}$	99.0	Direct data readout, tracking antenna
25.5-27.0 GHz (space-to-Earth)	EESS	Digital	$\geq 5$	$10^{-5}$	99.9	Direct high-speed data readout and recorded data acquisition, stored mission data

*Notes to Table 1:*

NOTE 1 – In Table 1, for the band 137-138 MHz, the elevation angle of  $25^\circ$  and other parameters for analogue receivers correspond with a level of performance that is guaranteed by designers of some systems. The parameters for the digital receivers correspond with user requirements.

NOTE 2 – The EESS is only allocated in the 1 690-1 710 MHz portion of the band.

NOTE 3 – Additional performance objectives could be specified for an availability of 99.99% of the time in relation to the need to synchronize the receiver to the data transmission frames and to avoid bit slips within a frame. However, for the purpose of deriving interference criteria, these objectives can be assumed to be met if the objectives associated with the above specified lower availability levels (Table 1) are met.

NOTE 4 – In all cases in Table 1, it is assumed that earth station sites are selected to yield average levels of environmental radio-frequency noise within the band. For direct data readout stations, which may be deployed in large numbers by various operating entities, there is a risk that randomly selected sites will exhibit higher than average levels of environmental noise (especially man-made noise) that may hamper the ability to achieve the stated performance objectives. However, the variance of this noise over all locations is not large in relation to receiver thermal noise, even at frequencies as low as 137-138 MHz, such that the performance objectives can generally be met at over 95% of the possible locations given link power margins of a few decibels. In the case of recorded data acquisition stations, sites are carefully selected to avoid ambient noise levels that exceed the average level.

TABLE 2

## Performance objectives for links in the EESS and MetSat using geostationary orbits

Frequency band	Satellite service	Modulation	Applicable elevation angle (degrees)	Minimum <i>C/N</i> or maximum BER	Required time availability (%)	Function and type of earth station
401-403 MHz (Earth-to-space)	MetSat and EESS	Digital	$\geq 3$	$10^{-5}$	99.6	Data collection, Low-gain antenna
460-470 MHz (space-to-Earth)	MetSat and EESS	Digital	$\geq 3$	$10^{-5}$	99.6	DCP interrogation, low-gain antenna
1 670-1 710 MHz (space-to-Earth)	MetSat and EESS	Digital	$\geq 3$	$10^{-6}$	99.9	Direct data readout and data dissemination, high-gain antenna
		Analogue	$\geq 3$	10 dB	99.9	Data dissemination, high-gain antenna
		Digital	$\geq 3$	$10^{-6}$	99.6	CDA station, high-gain antenna
2 025-2 110 MHz (Earth-to-space)	EESS	Digital	$\geq 3$	$10^{-5}$	99.6	CDA station, high-gain antenna
7 450-7 550 MHz (space-to-Earth)	MetSat	Digital	$\geq 5$	$10^{-6}$	99.9	Direct data readout, high-gain antenna
18.1-18.3 GHz (space-to-Earth)	MetSat	Digital	$\geq 5$	$10^{-7}$	99.9	Direct data readout, high-gain antenna
25.5-27.0 GHz (space-to-Earth)	EESS	Digital	$\geq 5$	$10^{-7}$	99.9	Direct data readout, high-gain antenna

*Notes to Table 2:*

NOTE 1 – Performance objectives for specific systems may differ from the objectives presented in this Recommendation; however, the objectives defined herein are used as a basis for deriving permissible levels of interference that are the minimum interference thresholds to be accepted by specific systems.

NOTE 2 – Additional performance objectives could be specified for an availability of 99.99% of the time in relation to the need to synchronize the receiver to the data transmission frames and to avoid bit slips within a frame. However, for the purpose of deriving interference criteria, these objectives can be assumed to be met if the objectives associated with the above availability levels are met.

NOTE 3 – The EESS is only allocated in the 1 690-1 710 MHz portion of the band.

NOTE 4 – In all cases in Table 2, it is assumed that earth station sites are selected to yield average levels of environmental radio-frequency noise within the band. For direct data readout stations, which may be deployed in large numbers by various operating entities, there is a risk that randomly selected sites will exhibit higher than average levels of environmental noise (especially man-made noise) that may hamper the ability to achieve the stated performance objectives. However, the variance of this noise over all locations is not large in relation to receiver thermal noise, such that the performance objectives can generally be met at over 95% of the possible locations given link power margins of a few decibels.

---