

International Telecommunication Union

**ITU-R**  
Radiocommunication Sector of ITU

**Recommendation ITU-R SA.1414-1**  
(12/2013)

**Characteristics of data relay  
satellite systems**

**SA Series**  
**Space applications and meteorology**

## Foreword

The role of the Radiocommunication Sector is to ensure the rational, equitable, efficient and economical use of the radio-frequency spectrum by all radiocommunication services, including satellite services, and carry out studies without limit of frequency range on the basis of which Recommendations are adopted.

The regulatory and policy functions of the Radiocommunication Sector are performed by World and Regional Radiocommunication Conferences and Radiocommunication Assemblies supported by Study Groups.

## Policy on Intellectual Property Right (IPR)

ITU-R policy on IPR is described in the Common Patent Policy for ITU-T/ITU-R/ISO/IEC referenced in Annex 1 of Resolution ITU-R 1. Forms to be used for the submission of patent statements and licensing declarations by patent holders are available from <http://www.itu.int/ITU-R/go/patents/en> where the Guidelines for Implementation of the Common Patent Policy for ITU-T/ITU-R/ISO/IEC and the ITU-R patent information database can also be found.

### Series of ITU-R Recommendations

(Also available online at <http://www.itu.int/publ/R-REC/en>)

Series	Title
<b>BO</b>	Satellite delivery
<b>BR</b>	Recording for production, archival and play-out; film for television
<b>BS</b>	Broadcasting service (sound)
<b>BT</b>	Broadcasting service (television)
<b>F</b>	Fixed service
<b>M</b>	Mobile, radiodetermination, amateur and related satellite services
<b>P</b>	Radiowave propagation
<b>RA</b>	Radio astronomy
<b>RS</b>	Remote sensing systems
<b>S</b>	Fixed-satellite service
<b>SA</b>	<b>Space applications and meteorology</b>
<b>SF</b>	Frequency sharing and coordination between fixed-satellite and fixed service systems
<b>SM</b>	Spectrum management
<b>SNG</b>	Satellite news gathering
<b>TF</b>	Time signals and frequency standards emissions
<b>V</b>	Vocabulary and related subjects

*Note: This ITU-R Recommendation was approved in English under the procedure detailed in Resolution ITU-R 1.*

Electronic Publication  
Geneva, 2014

© ITU 2014

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without written permission of ITU.

## RECOMMENDATION ITU-R SA.1414-1

**Characteristics of data relay satellite systems**

(Question ITU-R 118/7)

(1999-2013)

**Scope**

This Recommendation provides parameters for data relay satellite (DRS) systems worldwide to be used as guidance for deriving sharing criteria and coordination thresholds.

The ITU Radiocommunication Assembly,

*considering*

- a) that data relay satellite (DRS) systems operate as described in Recommendation ITU-R SA.1018 – Hypothetical reference system for systems comprising data relay satellites in the geostationary orbit and user spacecraft in low-Earth orbits;
- b) that there is an increase in mission requirements and in space research activity conducted particularly in low-Earth orbit;
- c) that DRS provide support to many programmes/missions in the space research service and are vital to supporting both manned and unmanned space research telecommunications;
- d) that it is necessary to establish relevant criteria for sharing between DRS systems and other services operating in co-frequency bands;
- e) that the technical characteristics of representative DRS systems need to be considered in order to derive relevant sharing criteria,

*recommends*

- 1** that the characteristics of DRS systems, as described in Annex 1, may be used in interference sharing studies;
- 2** that the information provided in Annex 1 should also be used as guidance for deriving sharing criteria and coordination thresholds as appropriate for DRS systems.

## Annex 1

## Characteristics of existing Data Relay Satellite (DRS) systems

TABLE 1

## Forward Earth-to-DRS feeder link characteristics

<i>Transmitting earth station</i>					
Network	Russian Federation	United States of America	Europe	Japan	China
Location	Russian Federation <sup>(1)</sup>	United States of America <sup>(1)</sup>	Europe	Japan	China
Frequency range (GHz)	14.5-15.34 selectable	14.6-15.25 selectable	28.6-29.8 selectable	29.5-31 selectable	29.4-30.2 selectable
Link description	Forward feeder-links Ku-band <sup>(5)</sup>	Composite <sup>(2)</sup>	Decentralized <sup>(3)</sup>	Decentralized <sup>(3), (4)</sup>	Composite <sup>(7)</sup>
Transmission rate	≤ 90 Mbit/s	≤ 25 Mbit/s	≤ 10 Mbit/s	≤ 50 Mbit/s	≤ 100 Mbit/s
Modulation	QPSK/SSM <sup>(6)</sup> , QPSK	PSK	PSK		
Polarization	Left-hand circular	Linear	Linear	Circular	Linear
Antenna size (m)	13.1	18.3	3 and 9	5, 9.2 and 13	3, 12 and 15
Tx antenna gain (dBi)	63.3	66.4	57.6 and 67.6	63, 68.2 and 71.4	56.9, 68.2 and 70.1
Tx antenna radiation pattern	Rec. ITU-R S.580	RR Appendix 8, Annex III			
Necessary bandwidth (MHz)	≤ 80 per channel	650 (composite)	≤ 100	≤ 978 (composite)	≤ 800 (composite)
Maximum power spectral density (dB(W/Hz))	-52.8	-58	-38	-32.5	-47
Maximum e.i.r.p. spectral density (dB(W/Hz))	10.5	8.8	19.6	38.9	23.1
<i>Receiving DRS</i>					
Orbital locations	160W, 16W, 95E, 167E	Rec. ITU-R SA.1275 or Rec. ITU-R SA.1276			
Antenna size (m)	0.6	1.8	0.4	2.0	1.5
Rx antenna gain (dBi)	36	47.0	40.2	53	49.5
Rx antenna radiation pattern	Rec. ITU-R S.672				
System noise temperature (K)	550	977	1 305	890 and 579	1 318
Link availability (%)	99.9	99.9	99.9	99.9	99.9
Interference criterion	Rec. ITU-R SA.1155				

<sup>(1)</sup> The earth stations for the Russian Federation network are located within the territory of the Russian Federation. The earth stations for the United States of America network are located in White Sands (New Mexico), Blossom Point (Maryland) and Guam. The coordinates of the stations are: 32.5° N, 106.60° W for White Sands; 38.43° N, 77.08° W for Blossom Point; and 13.62° N, 144.86° E for Guam.

<sup>(2)</sup> The composite link for the United States of America network is composed of seven channels: One DRS command and ranging channel, one DRS pilot tone signal, one S-band (2 GHz) multiple access (S-MA) link, two S-band single access (S-SA) links and two Ku-band (14/11 GHz and 30/20 GHz) single access (K-SA) links.

<sup>(3)</sup> The European DRS ground system consists of 12 earth stations, including the TT&C earth station, located in different countries within Europe. The earth station communicates with the DRS through its European coverage antenna.

<sup>(4)</sup> The Japanese network employs a decentralized link concept that permits independent forward feeder links from different earth stations.

<sup>(5)</sup> The Russian Federation DRS employs several independent forward feeder-links, including S-band (2 GHz) multiple access (S-MA) links, S-band single access (S-SA) links, Ku-band single access (Ku-SA) links and differential correction and monitoring system links that are augmented for the GLONASS system (GLONASS/SDCM).

<sup>(6)</sup> SSM: Spread-spectrum modulation.

<sup>(7)</sup> The Chinese networks implement a composite link concept that permits forward feeder links from different earth stations.

TABLE 2  
Forward DRS-to-spacecraft link characteristics

<i>Transmitting DRS</i>															
Network	Russian Federation	China	United States of America	Europe	Japan	United States of America	China	Russian Federation	Russian Federation	United States of America	Europe	Japan	United States of America	China	
Orbital locations	16W, 95E, 167E	Rec. ITU-R SA.1275 or Rec. ITU-R SA.1276					16W, 95E, 167E	160W, 16W, 95E, 167E	Rec. ITU-R SA.1275 or Rec. ITU-R SA.1276						
Frequency range (GHz)	2.025-2.110 <sup>(3)</sup>	2.090-2.098	2.103-2.110	2.025-2.110 <sup>(1)</sup>				13.4-13.8	13.750-13.800	22.55-23.55					
Link description	Multiple access (S-MA) links			Single access (S-SA) links				Single Access (Ku-SA) links			Single Access (Ka-SA) links				
Transmission rate (bit/s)	≤ 1 kbit/s	≤ 300 kbit/s 3 Mcps		≤ 1 Mbit/s	≤ 6 Mbit/s	≤ 300 kbit/s 3 Mcps	≤ 300 kbit/s 3 Mcps	≤ 64 kbit/s	≤ 40 Mbit/s	≤ 25 Mbit/s	≤ 10 Mbit/s	≤ 50 Mbit/s	≤ 25 Mbit/s	≤ 100 Mbit/s	
Modulation	QPSK/SSM <sup>(2)</sup>	PSK	SQPN/PSK <sup>(2)</sup>				PSK	QPSK/SSM <sup>(2)</sup>	QPSK	PSK					
Polarization	RHC	LHC	LHC	Circular				RHC	RHC	Circular					
Antenna size (m)	Phased array		Phased array	2.8	3.6	4.9	4.2	4	4	4.9	2.8	3.6	4.9	4.2	
Tx antenna gain (dBi)	14.3	26	26.0	34	36.4	36.0	35	35.0	51.8	51.2	53.4	57.4	54.7	56.5	
Tx antenna radiation pattern	Rec. ITU-R S.672	Rec. ITU-R S.672	Rec. ITU-R S.672												
Necessary bandwidth (MHz)	≤ 6	≤ 8	≤ 6	≤ 6	30	6	20	6	40	50	60	≤ 150	50	≤ 100	
Maximum power spectral density (dB(W/Hz))	-52.5	-46	-51.8	-54.7	-44.5	-55.3	-49.9	-56.4	-66.6	-79.7	-65.1	-49.5	-68.7	-64	
Maximum e.i.r.p. spectral density (dB(W/Hz))	-38.2	-20	-25.8	-20.7	-8.1	-19.3	-14.9	-21.4	-14.8	-28.5	-11.7	-7.9	-14.0	-7.5	

LHC – Left-hand circular; RHC – right-hand circular.

TABLE 2 (end)

<i>Receiving spacecraft</i>														
Network	Russian Federation	China	United States of America	Europe	Japan	United States of America	Russian Federation	China	Russian Federation	United States of America	Europe	Japan	United States of America	China
Orbital locations	Mainly low-Earth orbit													
Frequency range (GHz)	2.025-2.110 <sup>(3)</sup>	2.090-2.098	2.103-2.110	2.025-2.110 <sup>(1)</sup>					13.4-13.8	13.750-13.800	22.55-23.55			
Antenna size (m)	Omnidirectional, arrays			Omnidirectional, arrays, parabolic = $\leq 1.5$				Omnidirectional, arrays, parabolic = $\leq 0.8$	$\leq 1.2$	$\leq 1.5$	$\leq 1.3$		$\leq 1.3$	$\leq 0.8$
Rx antenna gain (dBi)	$\leq 1.5 / \leq 7.2$	$\leq 11$	$\leq 1.5$	$\leq 27.3$	$\leq 27.1$	$\leq 27.3$	$\leq 11$	$\leq 15$	$\leq 40.8$	$\leq 44$	$\leq 47$	$\leq 48.9$	$\leq 47$	$\leq 43$
Rx antenna radiation pattern		Rec. ITU-R S.672 for high gain antenna							Rec. ITU-R S.672					
System noise temperature (K)	450	600	600	600	680	600	450	600	550	1 000	1 400	850	1 400	1 400
Required $E_b/N_0$ (dB)	10.6	9.5	-9.5	9.5	10.5	9.5	10.6	9.5	10.6	9.5	9.5	10.8	9.5	9.5
Required BER	$1 \times 10^{-6}$	$1 \times 10^{-6}$	$1 \times 10^{-5}$	$1 \times 10^{-6}$	$1 \times 10^{-6}$	$1 \times 10^{-5}$	$1 \times 10^{-6}$	$1 \times 10^{-6}$	$1 \times 10^{-6}$	$1 \times 10^{-5}$	$1 \times 10^{-6}$		$1 \times 10^{-5}$	$1 \times 10^{-6}$
Link reliability (%)	99.9	99.9	99.99	99.9	99.9	99.99	99.9	99.9	99.9	99.9	99.9		99.9	99.9
Interference criterion	Rec. ITU-R SA.1155													

SQPN: Staggered quadriphase pseudo-random noise; SSM: Spread-spectrum modulation.

<sup>(1)</sup> Transmit frequency is selectable in 5 MHz steps,  $500 \times 221/240$  kHz steps for the Russian Federation DRS, 1 MHz steps for Chinese DRS.

<sup>(2)</sup> Signals with low data rate transmissions will be spread by a pseudo-random noise code so as to meet pfd limits.

<sup>(3)</sup> For the Russian Federation DRS transmit frequency is selectable in  $500 \times 221/240$  kHz steps.



TABLE 3  
Return spacecraft-to-DRS link characteristics

<i>Transmitting spacecraft</i>														
Network	Russian Federation	China	United States of America	Europe	Japan	United States of America	China	Russian Federation	Russian Federation	United States of America	Europe	Japan	United States of America	China
Orbital locations	Mainly low-Earth orbit													
Frequency range (GHz)	2.200-2.290 <sup>(3)</sup>	2.270-2.278	2.284-2.291	2.200-2.290 <sup>(1)</sup>				14.76-15.34	14.891-15.116	25.25-27.50				
Link description	Multiple access (S-MA) links			Single access (S-SA) links				Single access (Ku-SA) links		Single access (Ka-SA) links				
Transmission rate	≤ 1 kbit/s	≤ 300 kbit/s 3 Mcps	≤ 3 Mbit/s	≤ 1 Mbit/s	≤ 12 Mbit/s	≤ 6 Mbit/s	≤ 2 Mbit/s	≤ 64 kbit/s	≤ 90 Mbit/s	≤ 300 Mbit/s	≤ 150 Mbit/s	≤ 300 Mbit/s	≤ 800 Mbit/s	≤ 600 Mbit/s
Modulation	QPSK/SSM	PSK	SQPN/PSK <sup>(2)</sup>				PSK	QPSK/SSM	QPSK	PSK				
Polarization	RHC	LHC	LHC	Circular				RHC	RHC	Circular				
Antenna size (m)	Omnidirectional, arrays			Omnidirectional, arrays, parabolic = ≤ 1.5			Omnidirectional, arrays, parabolic = ≤ 0.8	Omnidirectional, arrays, parabolic = ≤ 1.5	≤ 1.2	≤ 1.5		≤ 1.9	≤ 1.5	≤ 0.8
Tx antenna gain (dBi)	≤ 1.5 / 7.2	≤ 11	≤ 15	≤ 27.3	≤ 27.6	≤ 27.3	≤ 15	≤ 11	≤ 42.2	≤ 43	≤ 47	≤ 49.7	≤ 47	≤ 44.5
Tx antenna radiation pattern	Rec. ITU-R S.672 for high gain antenna								Rec. ITU-R S.672					
Necessary bandwidth (MHz)	6	8	6	≤ 6	20	6	20	6	≤ 80 per channel	≤ 225	≤ 300	≤ 300	≤ 650	≤ 600
Maximum power spectral density (dB(W/Hz))	-55.8	-46	-60.8	-51	-55.7	-60.8	-46	55.8	-71.5	-73.5	-65.1	-58.8	-67.5	-50
Maximum e.i.r.p. spectral density (dB(W/Hz))	Compliant with pfd limits								-29.3	-30.5	-23	-9.1	-20.5	-5.5

TABLE 3 (end)

<i>Receiving DRS</i>															
Network	Russian Federation	China	United States of America	Europe	Japan	United States of America	China	Russian Federation	Russian Federation	United States of America	Europe	Japan	United States of America	China	
Orbital locations	16W, 95E, 167E	Rec. ITU-R SA.1275 or Rec. ITU-R SA.1276						16W, 95E, 167E	160W, 16W, 95E, 167E	Rec. ITU-R SA.1275 or Rec. ITU-R SA.1276					
Frequency range (GHz)	2.200-2.290 <sup>(1)</sup>	2.270-2.278	2.284-2.291	2.200-2.290 <sup>(1)</sup>				14.76-15.34	14.891-15.116	25.25-27.50					
Antenna size (m)	Horn	Phased array		2.8	3.6	4.9	4.2	4	4	4.9	2.8	3.6	4.9	4.2	
Rx antenna gain (dBi)	14.8	27	30.0	34.7	37.2	36.8	36.5	35.7	52.6	52.6	53.4	58.8	55.9	57.5	
Rx antenna radiation pattern	Rec. ITU-R S.672	Rec. ITU-R S.672	Rec. ITU-R S.672												
System noise temperature (K)	450	741	478	590	404	537	741	550	550	661	1 305	475	870	1 000	
Link reliability (%)	99.9	99.9	99.99		99.9	99.99	99.9	99.9	99.9	99.9	99.9		99.9	99.9	
Interference criterion	Rec. ITU-R SA.1155														

<sup>(1)</sup> Transmit frequency is selectable in 5 MHz steps for United States of America DRS, 100 kHz steps for Japanese DRS, 500 kHz for the Russian Federation DRS, 1 MHz steps for Chinese DRS.

<sup>(2)</sup> Signals with low data rate transmissions will be spread by a pseudo-random noise code so as to meet pfd limits.



TABLE 4  
Return DRS-to-Earth feeder link characteristics

<i>Transmitting DRS</i>					
Network	Russian Federation	United States of America	Europe	Japan	China
Orbital locations	160W, 16W, 95E, 167E	Rec. ITU-R SA.1275 or Rec. ITU-R SA.1276			
Frequency range (GHz)	10.7-10.95, 11.45-11.7, 12.5-12.75	13.4-14.05	18.1-21.2	19.7-21.2	18.9-21.2
Link description	Ku-band (14/11 GHz) return feeder	Ku-band (14/11 GHz) return feeder	Ka-band (30/20 GHz) return feeder		
Transmission rate (Mbit/s)	≤ 150 <sup>(3)</sup>	(1)	(2)	(2)	(4)
Modulation	QPSK, QPSK/SSM	PSK		SQPN/PSK	PSK
Polarization	RHC	Linear		Circular	Linear
Antenna size (m)	0.6	2	0.4	2.0	1.5
Tx antenna gain (dBi)	34.3	44.8	40.2	49.5	46.4
Tx antenna radiation pattern	Rec. ITU-R S.672				
Necessary bandwidth (MHz)	≤ 150 per channel	650 (composite), 225 (dedicated)	≤ 300	839	≤ 2 300 (composite)
Maximum power spectral density (dB(W/Hz))	-57.5	-58.6	-61	-40.9	-57.1
Maximum e.i.r.p. density (dB(W/Hz))	-23.2	-13.8	-20.8	8.6	-10.7
<i>Receiving earth station</i>					
Location	Russian Federation	United States of America	Europe	Japan	China
Antenna size (m)	13.1	18.3	3, 9	5, 9.2 and 13	3, 12 and 15
Rx antenna gain (dBi)	61.3	65.5	54, 63.9	59.5, 67.7	53.4, 65.5 and 67.1
Rx antenna radiation pattern	Rec. ITU-R S.580	RR Appendix 8, Annex III			
System noise temperature (K)	320	300	795	200	330
Link availability (%)	99.9	99.9	99.9		
Interference criterion	Rec. ITU-R SA.1155, Rec. ITU-R S.741	Rec. ITU-R SA.1155			

<sup>(1)</sup> The United States of America DRS transmits a dedicated and a composite link. Transmission rate for the dedicated link is 300 Mbit/s, for the composite link the transmission rate is on the order of 800 Mbit/s.

<sup>(2)</sup> The European and Japanese networks employ a decentralized link concept that permits independent return feeder links to different earth station.

<sup>(3)</sup> The Russian Federation DRS transmits several independent return feeder links within the indicated frequency range with transmission rates ≤ 150 Mbits/s.

<sup>(4)</sup> The Chinese networks implement a composite link concept that permits return feeder links to different earth stations.