

Description of EPFD validation and results of examination

Input parameters

Mask link data

Mask Id.	Direction	Minimum frequency, MHz	Maximum frequency, MHz	Linked orbit IDs / Satellite IDs
1	↓	17800	18600	All
2	↑	27600	28400	All
3	↔	17800	18600	All

Common SNS Data

Common

A.4.b.7.d.1 Exclusion zone type	A.4.b.7.d.1 Exclusion zone size, degrees
Y - topocentric angle (earth based)	5

Orbits

Apogee/Perigee/Inclination	A.4.b.6.d Uses station keeping	A.4.b.6.e Uses specific precession
8070/8070/51.6 8070/8070/90	Keeping	Default

Uplink

A.4.b.7.b Earth station density (1/km ²)	A.4.b.7.c Average distance (km)	A.4.b.7.a number of satellites receiving simultaneously
1E-06	999	1

Downlink

A.4.b.6.a Number of satellites transmitting to any latitude within corresponding range		
From latitude	To latitude	Number
-90	90	1

Group table

Beam(s)	Direction	Minimum frequency, MHz	Maximum frequency, MHz	A.4.b.7.cbis Minimum elevation angle
RKA	R	27600	28400	10
EKA	E	17800	18600	10

Results

B1A Beam designation	B2 Emi-Rcp	BR7a Group id./ Target Group id.	GHz	Orbital planes id. no.	Mask ID	Article 22 Limit	Result	Article 22 Examination
RKA	R	122670663 122670664	27.6-28.4	1 - 6	2	TABLE 22-2	Pass	Favorable
RKA	R	122670665 122670666	27.6- 28.0525	1 - 6	2	TABLE 22-2	Pass	Favorable
EKA	E	122670655 122670656 122670657 122670658	17.8-18.6	1 - 6	1, 3	TABLE 22-1B TABLE 22-3	Pass Pass	Favorable

Notes:

- Findings are promulgated as favorable when all applicable limits in Article 22 are met for given group of frequency assignments in all applicable scenarios.
- The Result column can be either Pass or Fail (see Rec. ITU-R S.1503-2). N/A (Non Applicable) refers to the case when an applicable Article 22 limit is not examined in the current scenario.

3. Qualified Favorable is established due to continuous application of Resolution 85 (WRC-03) on request by the notifying administration.