

HCS-5100PA Headphone



Features

- Used with the receiver or a conference unit
- Excellent sound quality
- 32 Ohm × 2, Ø 3.5 mm stereo plug (TRS)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW

Ordering Information

HCS-5100PA.....Headphone

HCS-5100PB Headphone (stereo)



Features

- Used with the receiver or a conference unit
- Excellent sound quality
- 32 Ohm × 2, Ø 3.5 mm stereo plug (TRS)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW

Ordering Information

HCS-5100PB.....Headphone

HCS-1020 Clip Microphone



Features

- Stylish and ergonomic design
- Excellent immunity to RF interferences from mobile phones
- Ø 3.5 mm stereo plug with a 1.5-meter cable

Technical Specifications

Electrical

Transducer.....Electret-condenser
 Polar pattern.....Uni-directional
 Operating voltage.....5 VDC
 Sensitivity.....-46 dBA at 680 Ohm (0 dB = 1 V/Pa at 1 kHz)
 Frequency response.....30 Hz to 20 kHz
 Input impedance.....2 kOhm
 Directivity 0°/180°.....> 20 dB (1 kHz)
 Equivalent noise.....20 dBA (SPL)
 Maximum sound pressure level.....125 dB (THD<3%)

Mechanical

Dimensions (h x w x d).....51 x 25 x 13 mm
 Weight.....3 g
 Color.....Black

Ordering Information

HCS-1020.....Clip Microphone