

ITU-T

G.8001/Y.1354

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

(04/2016)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA,
DIGITAL SYSTEMS AND NETWORKS

Packet over Transport aspects – Ethernet over Transport
aspects

SERIES Y: GLOBAL INFORMATION
INFRASTRUCTURE, INTERNET PROTOCOL ASPECTS
AND NEXT-GENERATION NETWORKS, INTERNET OF
THINGS AND SMART CITIES

**Terms and definitions for Ethernet frames over
transport**

Recommendation ITU-T G.8001/Y.1354

ITU-T G-SERIES RECOMMENDATIONS
TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS

INTERNATIONAL TELEPHONE CONNECTIONS AND CIRCUITS	G.100–G.199
GENERAL CHARACTERISTICS COMMON TO ALL ANALOGUE CARRIER-TRANSMISSION SYSTEMS	G.200–G.299
INDIVIDUAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON METALLIC LINES	G.300–G.399
GENERAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON RADIO-RELAY OR SATELLITE LINKS AND INTERCONNECTION WITH METALLIC LINES	G.400–G.449
COORDINATION OF RADIOTELEPHONY AND LINE TELEPHONY	G.450–G.499
TRANSMISSION MEDIA AND OPTICAL SYSTEMS CHARACTERISTICS	G.600–G.699
DIGITAL TERMINAL EQUIPMENTS	G.700–G.799
DIGITAL NETWORKS	G.800–G.899
DIGITAL SECTIONS AND DIGITAL LINE SYSTEM	G.900–G.999
MULTIMEDIA QUALITY OF SERVICE AND PERFORMANCE – GENERIC AND USER-RELATED ASPECTS	G.1000–G.1999
TRANSMISSION MEDIA CHARACTERISTICS	G.6000–G.6999
DATA OVER TRANSPORT – GENERIC ASPECTS	G.7000–G.7999
PACKET OVER TRANSPORT ASPECTS	G.8000–G.8999
Ethernet over Transport aspects	G.8000–G.8099
MPLS over Transport aspects	G.8100–G.8199
Synchronization, quality and availability targets	G.8200–G.8299
Service Management	G.8600–G.8699
ACCESS NETWORKS	G.9000–G.9999

For further details, please refer to the list of ITU-T Recommendations.

Recommendation ITU-T G.8001/Y.1354

Terms and definitions for Ethernet frames over transport

Summary

Recommendation ITU-T G.8001/Y.1354 provides definitions and abbreviations used in Ethernet frames over transport.

History

Edition	Recommendation	Approval	Study Group	Unique ID*
1.0	ITU-T G.8001/Y.1354	2006-06-06	15	11.1002/1000/8772
1.1	ITU-T G.8001/Y.1354 (2006) Amd. 1	2007-07-29	15	11.1002/1000/9172
2.0	ITU-T G.8001/Y.1354	2008-03-29	15	11.1002/1000/9391
3.0	ITU-T G.8001/Y.1354	2010-07-29	15	11.1002/1000/10898
4.0	ITU-T G.8001/Y.1354	2011-07-07	15	11.1002/1000/11135
5.0	ITU-T G.8001/Y.1354	2012-06-22	15	11.1002/1000/11510
6.0	ITU-T G.8001/Y.1354	2012-10-29	15	11.1002/1000/11783
7.0	ITU-T G.8001/Y.1354	2013-09-13	15	11.1002/1000/12001
8.0	ITU-T G.8001/Y.1354	2016-04-13	15	11.1002/1000/12802

Keywords

Abbreviation, acronym, definition, ethernet, terminology.

* To access the Recommendation, type the URL <http://handle.itu.int/> in the address field of your web browser, followed by the Recommendation's unique ID. For example, <http://handle.itu.int/11.1002/1000/11830-en>.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2016

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

Table of Contents

	Page
1 Scope.....	1
2 References.....	1
3 Definitions	1
3.1 Terms defined elsewhere	1
3.2 Terms defined in this Recommendation	1
4 Abbreviations and acronyms	8
Appendix I – List of source Recommendations.....	10
Bibliography.....	11

Recommendation ITU-T G.8001/Y.1354

Terms and definitions for Ethernet frames over transport

1 Scope

This Recommendation contains a complete listing of the definitions and abbreviations used in the Recommendations associated with Ethernet frames over transport.

2 References

None.

3 Definitions

3.1 Terms defined elsewhere

See Appendix I.

3.2 Terms defined in this Recommendation

This Recommendation defines the following terms:

3.2.1 backbone Ethernet connection: An Ethernet connection of which the traffic units are encapsulated with a backbone VLAN tag (B-Tag) when they are transported through an Ethernet link. Outside an Ethernet link, the traffic units are without a backbone VLAN tag; the information transported in the backbone VLAN tag is presented as a set of parameters: priority, drop eligible and EC identifier. The link end performs the mapping of those parameters into the backbone VLAN tag and the demapping of these parameters from the backbone VLAN tag.

NOTE – Backbone Ethernet connection is referred to in [b-ITU-T G.8012.1].

3.2.2 backbone service Ethernet connection: An Ethernet connection of which the traffic units are encapsulated with the first 48 bits of a backbone service instance tag (I-Tag) when they are transported through an Ethernet link. Outside an Ethernet link, the traffic units are without a backbone service instance tag; the information transported in the backbone service instance tag is presented as a set of parameters: priority, drop eligible and EC identifier. The link end performs the mapping of those parameters into the backbone service instance tag and the demapping of these parameters from the backbone service instance tag.

NOTE – Backbone service Ethernet connection is referred to in [b-ITU-T G.8012.1].

3.2.3 customer: The entity that has ownership authority over a set of flow points. The customer may have one or more service instances.

NOTE – Customer is referred to in [b-ITU-T G.8011].

3.2.4 customer Ethernet connection: An Ethernet connection (EC) of which the traffic units are encapsulated with a customer VLAN tag (C-Tag) when they are transported through an Ethernet link. Outside an Ethernet link, the traffic units are without a customer VLAN tag; the information transported in the customer VLAN tag is presented as a set of parameters: priority, drop eligible and EC identifier. The link end performs the mapping of those parameters into the customer VLAN tag and the demapping of these parameters from the customer VLAN tag.

NOTE – Customer Ethernet connection is referred to in [b-ITU-T G.8012.1].

3.2.5 dual-ended: A type of protocol messaging whereby an initiating MEP sends a request PDU to a receiving peer MEP, which does not send any response. In performance monitoring, the receiving MEP performs measurement calculations.

NOTE – Dual-ended is referred to in [b-ITU-T G.8013].

3.2.6 EoT-NNI: An NNI for the transfer of ETH_CI traffic units over a transport layer network.

NOTE – EoT-NNI is referred to in [b-ITU-T G.8012].

3.2.7 ERP instance: An entity that is responsible for the protection of a subset of the VLANs that transport traffic over the physical Ethernet ring. Each ERP instance is independent of other ERP instances that may be configured on the physical Ethernet ring.

NOTE – ERP instance is referred to in [b-ITU-T G.8032].

3.2.8 Ethernet management communication channel (ET.MCC): A function providing a management communication channel between a pair of maintenance entity group (MEG) end points (MEP). The MCC can be used to perform remote management. The specific use of MCC is outside the scope of this Recommendation. An MEP can send a frame with ETH-MCC information to its peer MEP with a remote maintenance request, remote maintenance reply, notification, etc. Configuration information needs to be provisioned to the MEP to support MCC functions. See [b-ITU-T G.8013] for detailed information and the protocol data unit (PDU) structure of the MCC.

NOTE – ET.MCC is defined in [b-ITU-T G.8051] as EoT MCC.

3.2.9 ETH_CI group: A group of ETH_CI signals that is monitored as a single MEG. For this purpose, ETH OAM is added to one of the ETH_CI signals in the group.

NOTE – ETH_CI group is referred to in [b-ITU-T G.8010].

3.2.10 ETH_CI traffic unit: The following set of signals defined in [b-ITU-T G.8010]: ETH_CI Data (D), ETH_CI priority (P), ETH_CI drop eligibility (DE), ETH_CI server signal fail (SSF) and optionally ETH_CI automatic protection switching (APS). The ETH_CI_D signal carries the traffic unit that consists of the following fields: destination address (DA), source address (SA) and MAC service data unit (M_SDU).

NOTE – ETH_CI traffic unit is defined in clause 6.3.1 of [b-ITU-T G.8010] and referred to in [b-ITU-T G.8012].

3.2.11 Ethernet flow replication point (ETHF_PP): Connection point between <Srv>/ETH adaptation source and sink. ETH_CI from source Ethernet flow point (ETH_FP) is replicated and delivered across ETHF_PP to sink Ethernet termination flow point (ETH_TFP).

NOTE – ETHF_PP is referred to in [b-ITU-T G.8021].

3.2.12 Ethernet replicated information (ETH_PI): Replicated ETH_CI delivered across ETHF_PP or ETH_TFP.

NOTE – ETH_PI is referred to in [b-ITU-T G.8021].

3.2.13 Ethernet ring: A collection of Ethernet ring nodes forming a closed physical loop whereby each Ethernet ring node is connected to two adjacent Ethernet ring nodes via a duplex communications facility.

NOTE – Ethernet ring is referred to in [b-ITU-T G.8032].

3.2.14 Ethernet ring node: A network element that implements at least the following functionality.

- a) One Ethernet connection function (ETH_C) with a dedicated Ethernet flow forwarding function (ETH_FF) for forwarding ring automatic protection switching (R-APS) control traffic.
- b) Two ring ports, including ETHDi/ETH adaptation function at the ring maintenance entity group level (MEL).
- c) Ethernet ring protection (ERP) control process controlling the blocking and unblocking of traffic over the ring ports.

NOTE – Ethernet ring node is referred to in [b-ITU-T G.8032].

3.2.15 Ethernet service: An Ethernet service supports an Ethernet flow (as specified in [b-ITU-T G.8010]). It is determined by the topology of the Ethernet network and a corresponding set of attributes associated with the Ethernet connection (EC), the UNI ports and NNI ports.

NOTE – Ethernet service is referred to in [b-ITU-T G.8011].

3.2.16 Ethernet termination flow replication point (ETHTF_PP): Connection point between <Srv>/ETH adaptation source and sink. ETH_CI from source Ethernet termination flow point (ETH_TFP) is replicated and delivered across ETHTF_PP to sink filter process.

NOTE – ETHTF_PP is referred to in [b-ITU-T G.8021].

3.2.17 Ethernet virtual connection (EVC)

NOTE – EVC is defined in [b-MEF 10.3].

3.2.18 ETH path: The highest ETH MEG level in a set of eight MEG levels.

NOTE – ETH path is referred to in [b-ITU-T G.8010].

3.2.19 ETH section: The lowest ETH MEG level in a set of eight MEG levels.

NOTE – ETH section is referred to in [b-ITU-T G.8010].

3.2.20 ETH tandem connection: An intermediate ETH MEG level in a set of eight MEG levels.

NOTE – ETH tandem connection is referred to in [b-ITU-T G.8010].

3.2.21 ET management network (ET.MN): A subset of a TMN that is responsible for managing those parts of a network element that contain ET layer network entities. An ET.MN may be subdivided into a set of ET management subnetworks.

NOTE – ET.MN is referred to in [b-ITU-T G.8051].

3.2.22 ET management subnetwork (ET.MSN): Subnetwork consisting of a set of separate embedded communication channels (ECCs) and associated intra-site data communication links which are interconnected to form a data communication network (DCN) within any given ET topology. For ET, the physical channel supporting the ECC is the Ethernet management communication channel (MCC) as defined in [b-ITU-T G.8013]. An ET.MSN represents an ET specific local communications network (LCN) portion of a network operator's overall data communication network or TMN.

NOTE – ET.MSN is referred to in [b-ITU-T G.8051].

3.2.23 ET network element (ET.NE): Element containing entities from one or more ET layer networks. An ET.NE may therefore be a stand-alone physical entity or a subset of a network element. It supports at least network element functions (NEFs) and may also support an operations system function (OSF). It contains managed objects (MOs), a message communication function (MCF) and a management application function (MAF). The functions of an ET.NE may be contained within an NE that also supports other layer networks. These layer network entities are considered to be managed separately from ET entities. As such, they are not part of the ET.MN or ET.MSN.

NOTE – ET.NE is referred to in [b-ITU-T G.8051].

3.2.24 Ety-NNI: An NNI for the transfer of ETH_CI traffic units over a physical Ethernet interface.

NOTE – Ety-NNI is referred to in [b-ITU-T G.8012].

3.2.25 Ety-UNI: A UNI for the transfer of ETH_CI traffic units over a physical Ethernet interface.

NOTE – Ety-UNI is referred to in [b-ITU-T G.8012].

3.2.26 external NNI (ENNI):

NOTE – ENNI is defined by [b-MEF 26.1].

3.2.27 far-end: In single-ended or dual-ended messaging, the direction and information relating to a one-way measurement from an initiating MEP) to a receiving or responding peer MEP.

NOTE – Far-end is referred to in [b-ITU-T G.8013].

3.2.28 initiating MEP: An initiating MEP initiates measurements by sending request PDUs, and in the case of single-ended messaging, receiving response PDUs.

NOTE – Initiating MEP is referred to in [b-ITU-T G.8013].

3.2.29 interconnection node: An Ethernet ring node that is common to two or more Ethernet rings or to a sub-ring and an interconnected network. At each interconnection node, there may be one or more Ethernet rings that can be accessed through a single ring port and not more than one Ethernet ring that is accessed by two ring ports. The former set of Ethernet rings is comprised of sub-rings, whereas the latter Ethernet ring is considered a major ring, relative to this interconnection node. If the interconnection node is used to connect a (set of) sub-ring(s) to another network, then there is no Ethernet ring accessed by two ring ports.

NOTE – Interconnection node is referred to in [b-ITU-T G.8032].

3.2.30 in-profile: For frames that belong to the same instance of an Ethernet service and priority, in-profile frames are defined as frames for which priority corresponds to a common value <X> and the network has determined that drop-eligibility corresponds to <false>. Procedures to determine drop-eligibility for a frame and procedures to convey priority and drop-eligibility on a frame are network and service specific.

NOTE – In-profile is referred to in [b-ITU-T G.8013].

3.2.31 in-service OAM: OAM actions that are carried out while the data traffic is not interrupted, with an expectation that data traffic remains transparent to OAM actions.

NOTE – In-service OAM is referred to in [b-ITU-T G.8013].

3.2.32 leaf group: A group representing two or more leaf ports within an RMP EC which can transmit to and receive from other leaves in the leaf group. Leaf ports within a leaf group cannot transmit to or receive from leaves outside the group.

NOTE – Leaf group is referred to in [b-ITU-T G.8012.1].

3.2.33 link Ethernet connection: An Ethernet connection of which the traffic units are either not encapsulated or encapsulated with a priority tag.

NOTE – Link Ethernet connection is referred to in [b-ITU-T G.8012.1].

3.2.34 maintenance entity: The entity between two of the flow/connection points in a maintenance entity group.

NOTE – Maintenance entity is referred to in [b-ITU-T G.8010].

3.2.35 maintenance entity group (MEG): A group defined, for the purpose of fragment or connection monitoring, between a set of flow or connection points within a fragment/connection. This set of flow or connection points may be located at the boundary of one administrative domain or a protection domain, or at the boundaries of two adjacent administrative domains. The maintenance entity group consists of one or more maintenance entities.

NOTE – MEG is referred to in [b-ITU-T G.8010].

3.2.36 maintenance entity group end point compound sink function: A compound transport processing function that accepts the characteristic information of the layer network at its input, extracts and processes the OAM information related to the monitoring of the maintenance entity group, filters the OAM information from within to the maintenance entity group, adapts the information and presents it as the characteristic information of the layer or a client layer at its output, potentially as a (client) layer maintenance signal (e.g., AIS).

NOTE – MEP compound sink function is referred to in [b-ITU-T G.8010].

3.2.37 maintenance entity group end point compound source function: A compound transport processing function that accepts the characteristic information of the layer or a client layer network at its input, adapts that information, filters it for OAM information interfering with its own OAM information, adds OAM information to allow the maintenance entity group to be monitored and presents the resulting information at its output.

NOTE – MEP compound source function is referred to in [b-ITU-T G.8010].

3.2.38 maintenance entity group intermediate point compound function: A compound transport processing function that accepts the characteristic information of the layer network at its input, reacts to OAM information related to on-demand monitoring of a maintenance entity group and presents the characteristic information without the OAM to which it reacted at its output.

NOTE – MIP compound function is referred to in [b-ITU-T G.8010].

3.2.39 major ring: An Ethernet ring that is connected on two ports to an interconnection node.

NOTE – Major ring is referred to in [b-ITU-T G.8032].

3.2.40 MEG end point (MEP): A point marking the end of an ETH MEG that is capable of initiating and terminating OAM frames for fault management and performance monitoring. A MEP does not add a new forwarding identifier to the transit ETH flows. A MEP does not terminate the transit ETH flows, though it can observe these flows (e.g., count frames).

NOTE – MEP is referred to in [b-ITU-T G.8013].

3.2.41 MEG intermediate point (MIP): An intermediate point in a MEG that is capable of reacting to some OAM frames. A MIP does not initiate OAM frames. A MIP takes no action on the transit ETH flows.

NOTE – MIP is referred to in [b-ITU-T G.8013].

3.2.42 near-end: In single-ended messaging, the direction and information relating to a one-way measurement from a responding peer MEP to an initiating MEP.

NOTE – Near-end is referred to in [b-ITU-T G.8013].

3.2.43 network termination: The network element in the transport network that is connected to the customer edge equipment.

NOTE – Network termination is referred to in [b-ITU-T G.8012].

3.2.44 network-to-network interface (NNI): An interface that is used for the interconnection of network elements within a transport network.

NOTE – NNI is referred to in [b-ITU-T G.8012].

3.2.45 on-demand measurement: A measurement (e.g., performance monitoring such as delay measurement, loss measurement) that is running at a specific request. An on-demand measurement has a defined start and end time or date.

NOTE – On-demand measurement is referred to in [b-ITU-T G.8052].

3.2.46 on-demand monitoring: A method to infer a specific status or performance characteristic of a maintenance entity or a set of maintenance entities within a maintenance entity group at a specific time with the purpose of obtaining a snapshot of the performance or to diagnose an identified fault condition or performance degradation.

NOTE – On-demand monitoring is referred to in [b-ITU-T G.8010].

3.2.47 on-demand OAM: OAM actions that are initiated via manual intervention for a limited time to carry out diagnostics. On-demand OAM can result in singular or periodic OAM actions during the diagnostics time interval.

NOTE – On-demand OAM is referred to in [b-ITU-T G.8013].

3.2.48 one-way: A measurement of the performance of frames that is achieved in one direction from an initiating MEP to a peer MEP, or vice versa; i.e., a unidirectional measurement.

NOTE – One-way is referred to in [b-ITU-T G.8013].

3.2.49 out-of-service OAM: OAM actions that are carried out while the data traffic is interrupted.

NOTE – Out-of-service OAM is referred to in [b-ITU-T G.8013].

3.2.50 operator virtual connection (OVC):

NOTE – OVC is defined by [b-MEF 26.1].

3.2.51 peer MEP: In a given MEP, all of the other MEPs in the same MEG.

NOTE – Peer MEP is referred to in [b-ITU-T G.8013].

3.2.52 proactive measurement: A measurement (e.g., performance monitoring such as delay measurement, loss measurement.) that is running continuously after it has been established. Proactive measurements can only be temporarily disabled.

NOTE – Proactive measurement is referred to in [b-ITU-T G.8052].

3.2.53 proactive monitoring: A method to continuously infer the status and performance of a maintenance entity group with the purpose of detecting disturbances, faults and degradations immediately after their occurrence in order to verify the service level agreement or initiate recovery actions to restore the service to the guaranteed level.

NOTE – Proactive monitoring is referred to in [b-ITU-T G.8010].

3.2.54 proactive OAM: OAM actions that are carried out continuously to permit proactive reporting of fault or performance results.

NOTE – Proactive OAM is referred to in [b-ITU-T G.8013].

3.2.55 R-APS virtual channel: The R-APS channel connection between two interconnection nodes of a sub-ring in (an)other Ethernet ring(s) or network(s). Its connection characteristics (e.g., path, performance) are influenced by the characteristics of the network (e.g., Ethernet ring) providing connectivity between the interconnection nodes.

NOTE – R-APS virtual channel is referred to in [b-ITU-T G.8032].

3.2.56 responding MEP: In single-ended messaging, an MEP that receives request PDUs from an initiating MEP and transmits corresponding response PDUs.

NOTE – Responding MEP is referred to in [b-ITU-T G.8013].

3.2.57 receiving MEP: In dual-ended messaging, an MEP that receives request PDUs from an initiating MEP, and does not respond to them.

NOTE – Receiving MEP is referred to in [b-ITU-T G.8013].

3.2.58 ring MEL: The maintenance entity group (MEG) level providing a communication channel for ring automatic protection switching (R-APS) information.

NOTE – Ring MEL is referred to in [b-ITU-T G.8032].

3.2.59 ring protection link (RPL): The ring link that under normal conditions, i.e., without any failure or request, is blocked (at one or both ends) to traffic channels, to prevent the formation of loops.

NOTE – Ring protection link is referred to in [b-ITU-T G.8032].

3.2.60 RPL neighbour node: When configured, an Ethernet ring node adjacent to the RPL that is responsible for blocking its end of the RPL under normal conditions (i.e., the ring is established and no requests are present in the ring) in addition to the block by the RPL owner node. However, it is not responsible for activating the reversion behaviour.

NOTE – RPL neighbour node is referred to in [b-ITU-T G.8032].

3.2.61 RPL owner node: An Ethernet ring node adjacent to the RPL that is responsible for blocking its end of the RPL under normal conditions (i.e., the ring is established and no requests are present in the ring). Furthermore, it is responsible for activating reversion behaviour from protected or manual switch/forced switch (MS/FS) conditions.

NOTE – RPL owner node is referred to in [b-ITU-T G.8032].

3.2.62 server MEP: A server MEP represents the compound function of the server layer termination function and server/ETH adaptation function, which is used to notify the ETH layer MEPs of conditions of the server layer that may be relevant to these ETH MEPs (e.g., failure or degradation detection by the server layer termination function or server/ETH adaptation function), where the server layer termination function is expected to run OAM mechanisms specific to that server layer.

NOTE – Server MEP is referred to in [b-ITU-T G.8013].

3.2.63 service Ethernet connection: An Ethernet connection of which the traffic units are encapsulated with a service VLAN tag (S-Tag) when they are transported through an Ethernet link. Outside an Ethernet link¹ the traffic units are without service VLAN tag; the information transported in the service VLAN tag is presented as a set of parameters: priority, drop eligible and EC identifier. The link end performs the mapping of those parameters into the service VLAN tag and the demapping of these parameters from the service VLAN tag.

NOTE – Service Ethernet connection is referred to in [b-ITU-T G.8012.1].

3.2.64 service frame:

NOTE – Service frame is defined in [b-MEF 10.3].

3.2.65 single-ended: A type of protocol messaging whereby an initiating MEP sends a request PDU to a responding peer MEP, and the peer MEP responds by sending a response PDU that contains the original request data plus any additional data added by the responder. In performance monitoring, the initiating MEP performs measurement calculations.

NOTE – Single-ended is referred to in [b-ITU-T G.8013].

3.2.66 sub-ring: An Ethernet ring that is connected to (an)other Ethernet ring(s) or network(s) through the use of a pair of interconnection nodes. On their own, the sub-ring links do not form a closed loop. A closed connection of traffic may be formed by the sub-ring links and one or more links, which are controlled by (an)other Ethernet ring(s) or network(s), between interconnection nodes.

NOTE – Sub-ring is referred to in [b-ITU-T G.8032].

3.2.67 sub-ring link: A span (e.g., link/port) connecting adjacent sub-ring nodes that are under the control of the Ethernet ring protection control process (ERP control process) of the sub-ring.

NOTE – Sub-ring link is referred to in [b-ITU-T G.8032].

3.2.68 two-way: A measurement of the performance of frames that is achieved from an initiating MEP to responding peer MEP, and back to the initiating MEP; i.e., a bidirectional or round-trip measurement.

NOTE – Two-way is referred to in [b-ITU-T G.8013].

3.2.69 traffic-conditioning function: A transport processing function that accepts the characteristic information of the layer network at its input, classifies the traffic units according to configured rules, meters each traffic unit within its class to determine its eligibility, polices non-conformant traffic units and presents the remaining traffic units at its output as characteristic information of the layer network.

NOTE – Traffic-conditioning function is referred to in [b-ITU-T G.8010].

¹ The term "Ethernet link" refers to the ETH link topological component specified in [b-ITU-T G.8010].

3.2.70 traffic-shaping function: A transport processing function that accepts the characteristic information of the layer network at its input, classifies the traffic units according to configured rules, meters each traffic unit within its class to determine its eligibility, controls non-conformant traffic units by buffering and scheduling them alternately with conformant traffic units for presentation at its output as characteristic information of the layer network.

NOTE – Traffic-shaping function is referred to in [b-ITU-T G.8021].

3.2.71 user network interface (UNI):

NOTE – User network interface is referred to in [b-MEF 10.3].

3.2.72 user-to-network interface (UNI): An interface that is used for the interconnection of customer equipment with a network element of the transport network.

NOTE – User-to-network interface is referred to in [b-ITU-T G.8012].

3.2.73 wait to block timer: A timer that is employed by the RPL owner to delay reversion after a forced switch or manual switch has been cleared.

NOTE – Wait to block timer is referred to in [b-ITU-T G.8032].

4 Abbreviations and acronyms

This Recommendation uses the following abbreviations and acronyms:

AIS	Alarm Indication Signal
APS	Automatic Protection Switching
B	Background
C	Customer
CI	Characteristic Information
D	Data
DA	Destination Address
DCN	Data Communication Network
DE	Drop Eligibility
EC	Ethernet Connection
ECC	Embedded Communication Channel
ENNI	External Network Network Interface
EoT	Ethernet over Transport
ERP	Ethernet Ring Protection
ET	Ethernet Transport
ET.MCC	ET Management Communication Channel
ET.MN	ET Management Network
ET.MSN	ET Management Subnetwork
ET.NE	ET Network Element
ETH	ETHERnet layer network
ETH_C	ETHERnet Connection function
ETH_CI	ETHERnet MAC Characteristic Information

ETH_CI_D	ETHERnet MAC Characteristic Information – Data
ETHDi	ETHERnet MAC layer network Diagnostic function within MIP
ETH_FF	Ethernet Flow Forwarding function
ETH_FP	ETHERnet Flow Point
ETHF_PP	ETHERnet Flow rePlication Point
ETHTF_PP	ETHERnet Termination Flow rePlication Point
ETH_TFP	ETHERnet Termination Flow Point
Ety-NNI	Ethernet NNI
Ety-UNI	Ethernet UNI
EVC	Ethernet Virtual Connection
I	Instance
LCN	Local Communications Network
MAC	Media Access Control
MAF	Management Application Function
MCC	Maintenance Communication Channel
MCF	Message Communication Function
M_SDU	MAC Service Data Unit
MEG	Maintenance Entity Group
MEL	MEG Level
MEP	MEG End Point
MIP	MEG Intermediate Point
MO	Managed Object
NE	Network Element
NEF	Network Element Function
NNI	Network Node Interface; Network-to-Network Interface
OAM	Operations, Administration and Maintenance
OSF	Operations System Function
OVC	Operator Virtual Connection
P	Priority
PDU	Protocol Data Unit
R-APS	Ring Automatic Protection Switching
RMP	Rooted MultiPoint
RPL	Ring Protection Link
SA	Source Address
SSF	Server Signal Fail
UNI	User Network Interface; User-to-Network Interface
VLAN	Virtual Local Area Network

Appendix I

List of source Recommendations

(This appendix does not form an integral part of this Recommendation.)

This edition of this Recommendation provides reference versions of abbreviations and terms from the Recommendations listed in Table I.1. Where the definitions were not a part of an explicit definitions clause of the source Recommendation, the source Recommendation is referenced in a Note following the definition. After this Recommendation is finally approved, corrigenda or revisions to the original sources of these terms will be proposed to replace the definitions in those documents by references to this one (except where the definition is part of the source Recommendation text and not in a definitions clause). The end result should be a single normative definition for each term in this subject area, contained in this Recommendation.

Table I.1 – Source Recommendations

ITU-T Recommendation	Latest version
ITU-T G.8010/Y.1306	02/2004 with Amd. 1 (2006), Err. 1 (2007), Err. 2 (2007) and Amd. 2 (2010).
ITU-T G.8011/Y.1307	01/2015
ITU-T G.8012/Y.1308	08/2004 with Amd.1 (2006)
ITU-T G.8012.1/Y.1308.1	12/2012
ITU-T G.8013/Y.1731	08/2015
ITU-T G.8021/Y.1341	04/2015 with Cor. 1 (2015)
ITU-T G.8032/Y.1344	08/2015 with G-Sup.52 (2012)
ITU-T G.8051/Y.1345	08/2015
ITU-T G.8052/Y.1346	08/2013

Bibliography

- [b-ITU-T G.800] Recommendation ITU-T G.800 (2012), *Unified functional architecture of transport networks*.
- [b-ITU-T G.805] Recommendation ITU-T G.805 (2000), *Generic functional architecture of transport networks*.
- [b-ITU-T G.808.1] Recommendation ITU-T G.808.1 (2014), *Generic protection switching – Linear trail and subnetwork protection*.
- [b-ITU-T G.809] Recommendation ITU-T G.809 (2003), *Functional architecture of connectionless layer networks*.
- [b-ITU-T G.870] Recommendation ITU-T G.870/Y.1352 (2012), *Terms and definitions for optical transport networks*.
- [b-ITU-T G.7710] Recommendation ITU-T G.7710/Y.1701 (2012), *Common equipment management function requirements*.
- [b-ITU-T G.7712] Recommendation ITU-T G.7712/Y.1703 (2010), *Architecture and specification of data communication network*.
- [b-ITU-T G.8010] Recommendation ITU-T G.8010/Y.1306 (2004), *Architecture of Ethernet layer networks*.
- [b-ITU-T G.8011] Recommendation ITU-T G.8011/Y.1307 (2015), *Ethernet service characteristics*.
- [b-ITU-T G.8012] Recommendation ITU-T G.8012/Y.1308 (2004), *Ethernet UNI and Ethernet NNI*.
- [b-ITU-T G.8012.1] Recommendation ITU-T G.8012.1/Y.1308.1 (2012), *Interfaces for the Ethernet transport network*.
- [b-ITU-T G.8013] Recommendation ITU-T G.8013/Y.1731 (2015), *Operations, administration and maintenance (OAM) functions and mechanisms for Ethernet-based networks*.
- [b-ITU-T G.8021] Recommendation ITU-T G.8021/Y.1341 (2015), *Characteristics of Ethernet transport network equipment functional blocks*.
- [b-ITU-T G.8031] Recommendation ITU-T G.8031/Y.1342 (2015), *Ethernet linear protection switching*.
- [b-ITU-T G.8032] Recommendation ITU-T G.8032/Y.1344 (2015), *Ethernet ring protection switching*.
- [b-ITU-T G.8051] Recommendation ITU-T G.8051/Y.1345 (2015), *Management aspects of the Ethernet transport (ET) capable network element*.
- [b-ITU-T G.8052] Recommendation ITU-T G.8052/Y.1346 (2013), *Protocol-neutral management information model for the Ethernet transport capable network element*.
- [b-ITU-T G-Sup.52] ITU-T G-series Recommendations – Supplement 52 (2012), *Ethernet ring protection switching*.
- [b-ITU-T M.3010] Recommendation ITU-T M.3010 (2000), *Principles for a telecommunications management network*; Amendment 2 (2005).

- [b-ITU-T M.3013] Recommendation ITU-T M.3013 (2000), *Considerations for a telecommunications management network*.
- [b-ITU-T M.3100] Recommendation ITU-T M.3100 (2005), *Generic network information model*.
- [b-ITU-T X.700] Recommendation ITU-T X.700 (1992), *Management framework for Open Systems Interconnection (OSI) for CCITT applications*.
- [b-ITU-T X.701] Recommendation ITU-T X.701 (1997) | ISO/IEC 10040:1998, *Information technology – Open Systems Interconnection – Systems management overview*.
- [b-MEF 10.3] MEF (2013), *Ethernet Services Attributes Phase 3*.
- [b-MEF 12.1] MEF (2010), *Carrier Ethernet Network Architecture Framework Part 2: Ethernet Services Layer – Basic Elements*.
- [b-MEF 26.1] MEF (2012), *External Network Network Interface (ENNI) – Phase 2*.

ITU-T Y-SERIES RECOMMENDATIONS

GLOBAL INFORMATION INFRASTRUCTURE, INTERNET PROTOCOL ASPECTS AND NEXT-GENERATION NETWORKS, INTERNET OF THINGS AND SMART CITIES

GLOBAL INFORMATION INFRASTRUCTURE	
General	Y.100–Y.199
Services, applications and middleware	Y.200–Y.299
Network aspects	Y.300–Y.399
Interfaces and protocols	Y.400–Y.499
Numbering, addressing and naming	Y.500–Y.599
Operation, administration and maintenance	Y.600–Y.699
Security	Y.700–Y.799
Performances	Y.800–Y.899
INTERNET PROTOCOL ASPECTS	
General	Y.1000–Y.1099
Services and applications	Y.1100–Y.1199
Architecture, access, network capabilities and resource management	Y.1200–Y.1299
Transport	Y.1300–Y.1399
Interworking	Y.1400–Y.1499
Quality of service and network performance	Y.1500–Y.1599
Signalling	Y.1600–Y.1699
Operation, administration and maintenance	Y.1700–Y.1799
Charging	Y.1800–Y.1899
IPTV over NGN	Y.1900–Y.1999
NEXT GENERATION NETWORKS	
Frameworks and functional architecture models	Y.2000–Y.2099
Quality of Service and performance	Y.2100–Y.2199
Service aspects: Service capabilities and service architecture	Y.2200–Y.2249
Service aspects: Interoperability of services and networks in NGN	Y.2250–Y.2299
Enhancements to NGN	Y.2300–Y.2399
Network management	Y.2400–Y.2499
Network control architectures and protocols	Y.2500–Y.2599
Packet-based Networks	Y.2600–Y.2699
Security	Y.2700–Y.2799
Generalized mobility	Y.2800–Y.2899
Carrier grade open environment	Y.2900–Y.2999
FUTURE NETWORKS	Y.3000–Y.3499
CLOUD COMPUTING	Y.3500–Y.3999
INTERNET OF THINGS AND SMART CITIES AND COMMUNITIES	
General	Y.4000–Y.4049
Definitions and terminologies	Y.4050–Y.4099
Requirements and use cases	Y.4100–Y.4249
Infrastructure, connectivity and networks	Y.4250–Y.4399
Frameworks, architectures and protocols	Y.4400–Y.4549
Services, applications, computation and data processing	Y.4550–Y.4699
Management, control and performance	Y.4700–Y.4799
Identification and security	Y.4800–Y.4899

For further details, please refer to the list of ITU-T Recommendations.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Environment and ICTs, climate change, e-waste, energy efficiency; construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Terminals and subjective and objective assessment methods
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks, Internet of Things and smart cities
Series Z	Languages and general software aspects for telecommunication systems