



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Series J
Supplement 1
(11/98)

SERIES J: TRANSMISSION OF TELEVISION, SOUND
PROGRAMME AND OTHER MULTIMEDIA SIGNALS

**Example of linking options between annexes of
ITU-T Recommendation J.112 and annexes of
ITU-T Recommendation J.83**

ITU-T J-series Recommendations – Supplement 1

(Previously CCITT Recommendations)

ITU-T J-SERIES RECOMMENDATIONS

TRANSMISSION OF TELEVISION, SOUND PROGRAMME AND OTHER MULTIMEDIA SIGNALS

General Recommendations	J.1–J.9
General specifications for analogue sound-programme transmission	J.10–J.19
Performance characteristics of analogue sound-programme circuits	J.20–J.29
Equipment and lines used for analogue sound-programme circuits	J.30–J.39
Digital encoders for analogue sound-programme signals	J.40–J.49
Digital transmission of sound-programme signals	J.50–J.59
Circuits for analogue television transmission	J.60–J.69
Analogue television transmission over metallic lines and interconnection with radio-relay links	J.70–J.79
Digital transmission of television signals	J.80–J.89
Ancillary digital services for television transmission	J.90–J.99
Operational requirements and methods for television transmission	J.100–J.109
Interactive systems for digital television distribution	J.110–J.129
Transport of MPEG-2 signals on packetised networks	J.130–J.139
Measurement of the quality of service	J.140–J.149
Digital television distribution through local subscriber networks	J.150–J.159

For further details, please refer to ITU-T List of Recommendations.

SUPPLEMENT 1 TO ITU-T J-SERIES RECOMMENDATIONS

EXAMPLE OF LINKING OPTIONS BETWEEN ANNEXES OF ITU-T RECOMMENDATION J.112 AND ANNEXES OF ITU-T RECOMMENDATION J.83

Source

Supplement 1 to ITU-T J-series Recommendations was prepared by ITU-T Study Group 9 (1997-2000) and was approved under the WTSC Resolution No. 5 procedure on the 19th of November 1998.

FOREWORD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation the term *recognized operating agency (ROA)* includes any individual, company, corporation or governmental organization that operates a public correspondence service. The terms *Administration*, *ROA* and *public correspondence* are defined in the *Constitution of the ITU (Geneva, 1992)*.

INTELLECTUAL PROPERTY RIGHTS

The ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. The ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, the ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 1999

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

INDEX

	<i>Page</i>
1 Introduction	1
2 Alternative global parameters for Annex B/J.112 to achieve linking.....	1
3 Alternative parameters for B.4.3/J.112 to achieve linking (the numbering of the subclauses is the same as in Recommendation J.112):	1

**EXAMPLE OF LINKING OPTIONS BETWEEN ANNEXES
OF ITU-T RECOMMENDATION J.112 AND ANNEXES
OF ITU-T RECOMMENDATION J.83**

(Geneva, 1998)

1 Introduction

Recommendation J.112 includes the statement in its clause 1 **Scope**, "There is therefore the possibility that, in application, the features chosen for use with the transmission system described in a particular annex of Recommendation J.83 are not limited to only the corresponding annex of this Recommendation." In particular, this Supplement defines an example of how to use Annex B/J.112 in conjunction with Annex A/J.83, by indicating the alternative parameters required for B.4.3/J.112 to achieve linking.

2 Alternative global parameters for Annex B/J.112 to achieve linking

In this example: in all cases, mention of Upstream Bandwidth "5 to 42 MHz" in Annex B/J.112 shall be read as "5 to 65 MHz"; and all mention of Downstream Bandwidth "95 to 857 MHz" shall be read as "100 to 860 MHz" throughout. In the case of Annex A/J.83, all mention of "6 MHz" shall be read as "8 MHz" throughout.

3 Alternative parameters for B.4.3/J.112 to achieve linking (the numbering of the subclauses is the same as in Recommendation J.112):

B.4.3 Downstream

B.4.3.1 Downstream protocol

The downstream PMD layer **MUST** conform to Annex A/J.83.

B.4.3.2 Scaleable interleaving to support low latency

Not required.

B.4.3.3 Downstream frequency plan

Shall meet national requirements.

B.4.3.4 CMTS output electrical

The CMTS **MUST** output an RF modulated signal with the following characteristics:

CMTS electrical output (Downstream)

Parameter	Value
Centre Frequency (f_c)	100 to 860 MHz \pm 30 kHz
Level	Adjustable over the range 50 to 61 dBmV
Modulation Type	64 QAM and 256 QAM
Symbol Rate (nominal) 64 QAM 256 QAM	6.952 Msym/s 6.952 Msym/s
Connector	F connector per IPS-SP-406

Byte/symbol mapping, differential coding and baseband filter characteristics are as in Annex A/J.83.

B.4.3.5 Downstream electrical input to CM

The CM MUST accept an RF modulated signal with the following characteristics:

Electrical input to CM

Parameter	Value
Centre Frequency	100 to 860 MHz \pm 30 kHz
Level Range (one channel)	-15 dBmV to +15 dBmV
Modulation Type	64 QAM and 256 QAM
Symbol Rate (nominal)	6.952 Msym/s (64 QAM) and 6.952 Msym/s (256 QAM)
Total Input Power (40-900 MHz)	< 30 dBmV
Input (load) Impedance	75 ohms
Input Return Loss	> 6 dB (100-860 MHz)
Connector	F connector per IPS-SP-406 (common with the output)

B.4.3.6 CM BER performance

The bit-error-rate performance of a CM MUST be as described in this subclause.

B.4.3.6.1 64 QAM

B.4.3.6.1.1 64 QAM CM BER performance

Implementation loss of the CM MUST be such that the CM achieves a post-FEC BER less than or equal to 10^{-8} when operating at a carrier to noise ratio (E_s/N_o) of 24.5 dB or greater.

B.4.3.6.1.2 64 QAM image rejection performance

Performance as described in B.4.3.6.1.1 MUST be met with analogue or digital signal at +10 dBc in any portion of the RF band other than the adjacent channels.

B.4.3.6.1.3 64 QAM adjacent channel performance

Performance as described in B.4.3.6.1.1 MUST be met with digital signal at 0 dBc in the adjacent channels.

Performance as described in B.4.3.6.1.1 MUST be met with analogue signal at +10 dBc in the adjacent channels.

Performance as described in B.4.3.6.1.1, with an additional 0.2 dB allowance, MUST be met with digital signal at +10 dBc in the adjacent channels.

B.4.3.6.2 256 QAM

B.4.3.6.2.1 256 QAM CM BER performance

Implementation loss of the CM MUST be such that the CM achieves a post-FEC BER less than or equal to 10^{-8} when operating at a carrier to noise ratio (E_s/N_o) of 31 dB or greater, with input signals greater than -6 dBmV.

B.4.3.6.2.2 256 QAM image rejection performance

Performance as described in B.4.3.6.2.1 MUST be met with analogue or digital signal at +10 dBc in any portion of the RF band other than the adjacent channels.

B.4.3.6.2.3 256 QAM adjacent channel performance

Performance as described in B.4.3.6.2.1 MUST be met with analogue or digital signal at 0 dBc in the adjacent channels.

Performance as described in B.4.3.6.2.1, with an additional 0.5 dB allowance, MUST be met with analogue signal at +10 dBc in the adjacent channels.

Performance as described in B.4.3.6.2.1, with an additional 1.0 dB allowance, MUST be met with digital signal at +10 dBc in the adjacent channels.

ITU-T RECOMMENDATIONS SERIES

Series A	Organization of the work of the ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure
Series Z	Languages and general software aspects for telecommunication systems