

Superseded by a more recent version



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

M.1380

(04/97)

SERIES M: TMN AND NETWORK MAINTENANCE:
INTERNATIONAL TRANSMISSION SYSTEMS,
TELEPHONE CIRCUITS, TELEGRAPHY, FACSIMILE
AND LEASED CIRCUITS

International data transmission systems

**Bringing-into-service of international leased
circuits that are supported by international data
transmission systems**

ITU-T Recommendation M.1380

Superseded by a more recent version

(Previously CCITT Recommendation)

Superseded by a more recent version

ITU-T M-SERIES RECOMMENDATIONS

TMN AND NETWORK MAINTENANCE: INTERNATIONAL TRANSMISSION SYSTEMS, TELEPHONE CIRCUITS, TELEGRAPHY, FACSIMILE AND LEASED CIRCUITS

Introduction and general principles of maintenance and maintenance organization	M.10–M.299
International transmission systems	M.300–M.559
International telephone circuits	M.560–M.759
Common channel signalling systems	M.760–M.799
International telegraph systems and phototelegraph transmission	M.800–M.899
International leased group and supergroup links	M.900–M.999
International leased circuits	M.1000–M.1099
Mobile telecommunication systems and services	M.1100–M.1199
International public telephone network	M.1200–M.1299
International data transmission systems	M.1300–M.1399
Designations and information exchange	M.1400–M.1999
International transport network	M.2000–M.2999
Telecommunications management network	M.3000–M.3599
Integrated services digital networks	M.3600–M.3999
Common channel signalling systems	M.4000–M.4999

For further details, please refer to ITU-T List of Recommendations.

Superseded by a more recent version

ITU-T RECOMMENDATION M.1380

BRINGING-INTO-SERVICE OF INTERNATIONAL LEASED CIRCUITS THAT ARE SUPPORTED BY INTERNATIONAL DATA TRANSMISSION SYSTEMS

Summary

This Recommendation is only applicable to international leased circuits that are supported by an international data transmission system.

The requirements described in this Recommendation should ensure that an international leased circuit meets performance expectations and is fully tested prior to introduction into service.

The bringing-into-service tests described in this Recommendation should ideally include periods of normal industrial activity to be representative of typical network conditions.

This Recommendation has been developed to be consistent with Recommendation M.1370 [10] that describes the bringing-into-service of international data transmission systems.

Recommendation M.1385 [11] covers maintenance issues for international leased circuits that are supported by an international data transmission system.

This Recommendation addresses the bringing-into-service requirements of leased circuits with a digital presentation at renters' premises. For circuits with an analogue presentation, the bringing-into-service procedures given in Recommendation M.1050 [7] apply, with performance achievement in accordance with Recommendations M.1020 [3], M.1025 [4] or M.1040 [5] as appropriate.

Source

ITU-T Recommendation M.1380 was revised by ITU-T Study Group 4 (1997-2000) and was approved under the WTSC Resolution No. 1 procedure on the 19th of April 1997.

Keywords

Bringing-into-service, international data transmission systems, international leased circuits, testing of performance objectives.

Superseded by a more recent version

FOREWORD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

INTELLECTUAL PROPERTY RIGHTS

The ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. The ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, the ITU had/had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 1997

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

Superseded by a more recent version

CONTENTS

	Page
1 Scope.....	1
2 References.....	1
3 Terminology and definitions.....	2
4 Performance limits and objectives.....	2
5 Preliminary exchange of information.....	3
6 Bringing-into-service procedures.....	3

Superseded by a more recent version

Recommendation M.1380

BRINGING-INTO-SERVICE OF INTERNATIONAL LEASED CIRCUITS THAT ARE SUPPORTED BY INTERNATIONAL DATA TRANSMISSION SYSTEMS

(Helsinki, 1993; revised in 1997)

1 Scope

This Recommendation describes the bringing-into-service procedures for an international leased circuit that is supported by an international data transmission system. The circuit will have a digital presentation, in the PDH domain, at the customer's premises.

This Recommendation does not cover the bringing-into-service requirements of leased circuits with an analogue presentation at the customer's premises. Such circuits are described in Recommendation M.1050.

2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. All Recommendations are subject to revision; all users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations listed below. A catalogue of the currently valid ITU-T Recommendations is regularly published.

- [1] ITU-T Recommendation M.60 (1993), *Maintenance terminology and definitions*.
- [2] ITU-T Recommendation M.1375 (1996), *Maintenance of international data transmission systems*.
- [3] ITU-T Recommendation M.1020 (1993), *Characteristics of special quality international leased circuits with special bandwidth conditioning*.
- [4] ITU-T Recommendation M.1025 (1993), *Characteristics of special quality international leased circuits with basic bandwidth conditioning*.
- [5] CCITT Recommendation M.1040 (1988), *Characteristics of ordinary quality international leased circuits*.
- [6] ITU-T Recommendation M.1045 (1996), *Preliminary exchange of information for the provision of international leased circuits and international data transmission systems*.
- [7] ITU-T Recommendation M.1050 (1993), *Lining up an international point-to-point leased circuit*.
- [8] CCITT Recommendation M.1300 (1992), *International data transmission systems operating in the range 2.4 kbit/s to 2048 kbit/s*.
- [9] ITU-T Recommendation M.1340 (1996), *Performance allocations and limits for international data transmission links and systems*.
- [10] ITU-T Recommendation M.1370 (1993), *Bringing-into-service of international data transmission systems*.
- [11] ITU-T Recommendation M.1385 (1993), *Maintenance of international leased circuits that are supported by international data transmission systems*.

Superseded by a more recent version

- [12] CCITT Recommendation M.1560 (1992), *Escalation procedure for international leased circuits.*
- [13] ITU-T Recommendation V.11 (1996), *Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s.*
- [14] ITU-T Recommendation V.24 (1996), *List of definitions for interchange circuits between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE).*
- [15] ITU-T Recommendation V.28 (1993), *Electrical characteristics for unbalanced double-current interchange circuits.*
- [16] CCITT Recommendation V.36 (1988), *Modems for synchronous data transmission using 60-108 kHz group band circuits.*
- [17] ITU-T Recommendation V.110 (1996), *Support of data terminal equipments with V-Series type interfaces by an Integrated Services Digital Network (ISDN).*
- [18] CCITT Recommendation X.21 (1992), *Interface between data terminal equipment and data circuit-terminating equipment for synchronous operation on public data networks.*
- [19] CCITT Recommendation G.703 (1991), *Physical/electrical characteristics of hierarchical digital interfaces.*
- [20] CCITT Recommendation G.702 (1988), *Digital hierarchy bit rates.*

3 Terminology and definitions

Recommendation M.1300 [8] provides general descriptions of international data transmission systems.

Terminology and definitions relating to this Recommendation are provided in Recommendation M.60 [1].

4 Performance limits and objectives

Performance limits for the international section should be consistent with those given in Recommendation M.1340 [9]. For all performance tests described in this Recommendation, the Errored Second (ES) and Severely Errored Second (SES) limits should be met simultaneously for the test result to be considered acceptable.

For the national circuit sections, limits will be set independently by the Administrations involved taking account of local conditions. Performance achievement will clearly be dependent upon the performance and topology of the local transmission facilities. To maintain consistency with Recommendation M.1340 [9], Administrations should use errored seconds and severely errored seconds parameters to measure performance achievement.

The possible development and application of performance objectives for transmission delay is left for further study.

All test results obtained during bringing-into-service tests should be retained for future reference during maintenance activities.

Superseded by a more recent version

5 Preliminary exchange of information

Consideration should be given to information that has already been exchanged for the international data transmission system that will support service. See clause 2/M.1370 [10].

Circuit information should be exchanged in accordance with Recommendation M.1045 [6]. In addition, Administrations may find that it is advantageous to exchange the following information:

- a) details of any special maintenance or fault reporting arrangements that have been requested (e.g. single end fault reporting);
- b) contact details for, and operational arrangements with, any additional Administrations that are involved with the provision of service (e.g. Administrations that provide a transit routing facility);
- c) precise details of the interface presentation and functionality at the renter's premises (this should ideally be in accordance with existing Recommendations, e.g. V.11 [13], X.21 [18], V.24 [14], V.28 [15], V.36 [16], V.110 [17], G.703 [19]);
- d) performance limits for the national sections (see below) and for the overall circuit;
- e) confirmation of the data rate presented at the customer interface where this is different to the data rate extended internationally (e.g. application of Recommendation G.702 [20] for the support of 1544 kbit/s circuits within a 2048 kbit/s transmission hierarchy);
- f) details of any equipment loopback capabilities that may be available;
- g) details of escalation arrangements and contacts that may be used to overcome operational difficulties (see Recommendation M.1560 [12]).

Administrations should confirm that the information exchanged is consistent and that the circuit will be able to support service.

The information that has been exchanged, as detailed above, should be retained for future reference.

6 Bringing-into-service procedures

It is normal practice to set up the national circuit sections prior to attempting to test the international section.

Suitable performance limits for the national circuit sections should be developed and exchanged between the Administrations involved [see item d) of clause 5 above].

When the national circuit sections have been provided and successfully tested, the international section (international data transmission system channel) should be tested. If in-service performance monitoring is available, and the error performance of the international data transmission system is acceptable, all new circuits should be tested for 15 minutes. In the case where a number of circuits are brought into service at the same time, and in-service performance monitoring is not available, the first circuit should be tested for 24 hours, and the remaining circuits could be tested for 15 minutes each. The objectives given in clause 4/M.1340 [9] should be met. Where there is little confidence regarding the capabilities of a particular international data transmission system, or where the short duration test objectives were not met, a 24-hour test should be performed using the limits that were originally developed to test the international data transmission system (see clause 3/ M.1370 [10]). In the event that the 24 hour limits are not met, Administrations should agree to an appropriate course of action (see Recommendation M.1375 [2] for guidance).

Any portions of the circuit which are not supported by the international data transmission system should be tested for 24 hours.

Superseded by a more recent version

Where the international section extends significantly beyond the channel interfaces of a particular international data transmission system (e.g. where a transit routing involves the interconnection of two international data transmission systems), additional tests may be required. Administrations should ensure that all parts of the international section are fully tested. Suitable additional limits should be agreed between the Administrations involved. Consistency with Recommendation M.1340 [9] should be sought wherever possible.

It will normally be advantageous to perform an end-to-end test to confirm overall integrity and stability. A 24-hour test duration is recommended. Test limits should include allowances for the international and two national circuit sections. Administrations should pay particular attention to highlighting any problems that may be associated with the interworking of separately timed networks, especially for the first circuit provision that uses a particular equipment configuration.

Dependent upon the loopback capabilities provided by the network terminating equipments at the renter's premises, it may be possible to perform end-to-end tests from intermediate points within the network (e.g. at terminal international centres).

Where loop tests are employed, it is proposed that no special additional performance allowance is made (i.e. doubling of limits is not recommended).

Superseded by a more recent version

ITU-T RECOMMENDATIONS SERIES

Series A	Organization of the work of the ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communication
Series Z	Programming languages