

International Telecommunication Union

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

T.808

Corrigendum 1
(01/2007)

SERIES T: TERMINALS FOR TELEMATIC SERVICES

Information technology – JPEG 2000 image coding system: Interactivity tools, APIs and protocols

Technical Corrigendum 1

ITU-T Recommendation T.808 (2005) – Technical Corrigendum 1



**Information technology – JPEG 2000 image coding system:
Interactivity tools, APIs and protocols**

Technical Corrigendum 1

Summary

ITU-T Rec. T.808 | ISO/IEC 15444-9 specifies JPIP, the JPEG 2000 client/server communication protocol. Corrigendum 1 provides corrections and clarifications for the metadata transfers between the server and client and for the colour space method preferences.

Source

Corrigendum 1 to ITU-T Recommendation T.808 (2005) was approved on 13 January 2007 by ITU-T Study Group 16 (2005-2008) under the ITU-T Recommendation A.8 procedure. An identical text is also published as Technical Corrigendum 1 to ISO/IEC 15444-9.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2007

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

CONTENTS

	<i>Page</i>
1) Annex A.3.2.1.....	1
2) Annex A.3.3	1
3) Annex A.3.6.1.....	1
4) Annex C.3.4	1
5) Annex C.5.1	2
6) Annex C.7.2	2
7) Annex C.8.1.3.....	2
8) Annex C.10.2.3.....	2

**INTERNATIONAL STANDARD
ITU-T RECOMMENDATION**

**Information technology – JPEG 2000 image coding system:
Interactivity tools, APIs and protocols**

Technical Corrigendum 1

1) Annex A.3.2.1

Add the following note at the end of the clause:

NOTE – For the sake of efficiency when serving an image containing PPM markers, a server may transcode the packed packet headers in the main header into the tile headers (PPT markers). Otherwise, a client would require tile-part length markers (TLM) to be sent. The server may alternatively transcode the image (transparently to the client) in such a way as to avoid the use of packed packet headers altogether.

2) Annex A.3.3

Replace the sentence:

This data bin may be formed from a legal codestream, by concatenating all marker segments except SOT and POC in all tile-part headers for tile *n*.

with:

This data bin may be formed from a legal codestream, by concatenating all marker segments except SOT in all tile-part headers for tile *n*.

NOTE 1 – POC marker segments may also be removed as they are not required by a typical JPIP client. However, a server might need to include the POC markers for a client application that was to output a JPEG 2000 file with the same progression order as the original image available at the server.

A server may send data in any order, but must send a tile header data bin for a tile even if the tile header is empty.

NOTE 2 – A client that receives image data for a tile but has not yet received its tile header should not assume that the tile header is empty and attempt to decode the data. It might be beneficial for certain clients to receive the tile header bin in advance of the tile data bin.

3) Annex A.3.6.1

Add the following sentence at the end of the clause:

A server is required to send at least the metadata bin with bin Id 0, even if no metadata is present. In this case, the metabin #0 will be empty.

NOTE 2 – A client should not assume that no metadata is available if it has not yet received any metadata bin. It might be beneficial for certain clients to receive the metadata bin with bin Id 0 in advance to all other bins.

4) Annex C.3.4

Add the following note at the end of the clause:

NOTE – The combination of "wait = yes" with "cclose=*" is not recommended. If this situation is encountered, the application can decide which of the two takes priority.

5) Annex C.5.1

Replace the following sentence at the end of the first paragraph:

Where the server is aware of additional relevant metadata elements, it may deliver these as well.

with the following note:

NOTE – The list of boxes defined in this clause is not exhaustive. Additional boxes may be required to decode the requested view window within the logical target correctly.

6) Annex C.7.2

Add the following note at the end of the clause:

NOTE – The combination of "wait = yes" with "cclose=*" is not recommended. If this situation is encountered, the application can decide which of the two takes priority.

7) Annex C.8.1.3

The following sentence should be added to the beginning of the first paragraph:

Implicit bin-descriptors are only applicable to JPP-stream requests.

8) Annex C.10.2.3

Change the contents of the boxes "Use unmodified value" and "Use modified value" of Figure C.3 as follows:

Change:

Use unmodified value

$priority[i] = spec[i].APPROX + spec[i].PREC$

to:

Use unmodified value

$priority[i] = spec[i].APPROX + 256 - spec[i].PREC$

Change:

Use modified value

$priority[i] = 1 + spec[i].PREC$

to:

Use modified value

$priority[i] = 257 - spec[i].PREC$

The body of the text shall remain unaltered.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks
Series Z	Languages and general software aspects for telecommunication systems