

International Telecommunication Union

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

T.808

Corrigendum 2

(06/2008)

SERIES T: TERMINALS FOR TELEMATIC SERVICES

Still-image compression – JPEG 2000

Information technology – JPEG 2000 image coding
system: Interactivity tools, APIs and protocols

**Technical Corrigendum 2: Clarifications to the
metadata transfers between server and client**

Recommendation ITU-T T.808 (2005) – Technical
Corrigendum 2



ITU-T T-SERIES RECOMMENDATIONS
TERMINALS FOR TELEMATIC SERVICES

Facsimile – Framework	T.0–T.19
Still-image compression – Test charts	T.20–T.29
Facsimile – Group 3 protocols	T.30–T.39
Colour representation	T.40–T.49
Character coding	T.50–T.59
Facsimile – Group 4 protocols	T.60–T.69
Telematic services – Framework	T.70–T.79
Still-image compression – JPEG-1, Bi-level and JBIG	T.80–T.89
Telematic services – ISDN Terminals and protocols	T.90–T.99
Videotext – Framework	T.100–T.109
Data protocols for multimedia conferencing	T.120–T.149
Telewriting	T.150–T.159
Multimedia and hypermedia framework	T.170–T.189
Cooperative document handling	T.190–T.199
Telematic services – Interworking	T.300–T.399
Open document architecture	T.400–T.429
Document transfer and manipulation	T.430–T.449
Document application profile	T.500–T.509
Communication application profile	T.510–T.559
Telematic services – Equipment characteristics	T.560–T.649
Still-image compression – JPEG 2000	T.800–T.849
Still-image compression – JPEG-1 extensions	T.850–T.899

For further details, please refer to the list of ITU-T Recommendations.

**Information technology – JPEG 2000 image coding system:
Interactivity tools, APIs and protocols**

**Technical Corrigendum 2
Clarifications to the metadata transfers between server and client**

Summary

Corrigendum 2 to Recommendation ITU-T T.808 | ISO/IEC 15444-9 provides clarifications to the metadata transfers between server and client.

Source

Corrigendum 2 to Recommendation ITU-T T.808 (2005) was approved on 13 June 2008 by ITU-T Study Group 16 (2005-2008) under Recommendation ITU-T A.8 procedure. An identical text is also published as Technical Corrigendum 2 to ISO/IEC 15444-9.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2008

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

INTERNATIONAL STANDARD
RECOMMENDATION ITU-TInformation technology – JPEG 2000 image coding system:
Interactivity tools, APIs and protocolsTechnical Corrigendum 2
Clarifications to the metadata transfers between server and client

1) Subclause C.5.2

Replace the entire body of C.5.2 by the following text:

C.5.2 Metadata Request (metareq)

C.5.2.1 Description

```
metareq = "metareq" "=" 1#("[ 1$(req-box-prop) "]" [root-bin] [max-depth])
                                     [metadata-only]
req-box-prop = box-type [limit] [metareq-qualifier] [priority]
limit = ":" (UINT / "r")
metareq-qualifier = "/" 1*("w" / "s" / "g" / "a")
priority = "!"
root-bin = "R" UINT
max-depth = "D" UINT
metadata-only = "!!"
```

This field specifies what metadata is desired in response to a request, in addition to any metadata required for the client to decode or interpret the requested image data as defined by C.5.1. The purpose of this request is to allow the client to request selected parts of the contents and the layout of the metadata encoded in the JP2 and JPX file formats a server did not choose to transmit according to C.5.1.

The value string in this request field is a list of independent requests; however, the server may handle the requests as a group, and there may be overlap between the requests. It is then sufficient (but not necessary) that the server sends the requested data only once.

The way how the server decides to break up the initial stream into bins is irrelevant for defining the target of the request except that the `root-bin` field can be used to limit a request to parts of the file structure, once a client has identified the layout. Once a request is confined to a specific bin, the way how that bin is broken up into more bins – or if it is broken up at all – is irrelevant for the client and the way how that data is addressed within the request.

Note, however, that data a server returns upon a request will, in general, depend on that layout because the division of the logical target into metadata-bins may force the server to return additional data, including the contents or headers of some other, potentially unrequested boxes. All a server has to ensure that **at least** the requested data is contained, and that **enough** data is returned to allow a client to parse it. Examples when additional data must be returned are given below in C.5.2.7. The following text uses the wording "request" to point out which data is **desired** by the client, which might be a sub-set of the data actually returned by the server due to reasons pointed out in C.5.2.7.

Example

For better illustration, examples in the following subclauses all refer to the following segment of a JPX file, see Rec. ITU-T T.801 | ISO/IEC 15444-2 for the definition of the boxes used here. The labels on the right-hand side have been added for later reference:

Content	Label
association box header ('asoc')	A
number list box header ('nlst')	B
number list box content	C
association box header ('asoc')	D
ROI description box header ('roid')	E
ROI description box content	F
association box header ('asoc')	G
label box header ('lbl\040')	H
label box content	I
XML box header ('xml\040')	J
XML box content	K

The sub-box structure of the above example is indicated by indentation, e.g., items H to K establish the contents of the superbox at label G.

C.5.2.2 root-bin

Each request is relative to the data-bin specified by its `root-bin` value. If a `root-bin` value is not specified, the root is meta-data bin 0. The request pertains only to data within or referenced by that particular data-bin.

Example

If the server decided to place the contents of association box 'A' in the above example into a separate bin with bin id #3, the association box header 'A' would be encoded in a placeholder box, and items 'B' to 'K' would establish bin #3. In that case, a `root-bin` field of 3 would limit the scan to items 'B' to 'K' only. Specifically, `metareq=[roid]R3` would request items 'E' and 'F' from the server and no other data outside of this example (but see also C.5.2.3 and C.5.2.7 for additional data outside of the request potentially returned by the server along).

An alternative layout might be to include items 'B' to 'G' in bin #3 as above, but in addition place items 'H' to 'K' into the separate bin #4. Thus 'G' would be represented by a placeholder box in bin #3 and 'H' to 'K' would be part of bin #4. A `root-bin` field of 3 would still scan the items 'H' to 'K' because they are referenced by a placeholder in bin #3 and the way how bin #3 is broken up into sub-bins is irrelevant to the request. Thus, even though the server response would be different, the items identified by the request remain the same.

A `root-bin` field of 0 imposes no further restriction on the request each item, box or superbox, is somehow reachable from the metadata-bin #0. Whether placeholder boxes are used or not is completely irrelevant. Thus, `metareq=[roid]` would request all ROI description boxes from the server, and thus also include items 'E' and 'F' along with all other ROI description boxes available.

C.5.2.3 max-depth

If a value for `max-depth` is specified, then only boxes contained within the root metadata-bin, and those no more than `max-depth` levels in the file hierarchy below that box are requested. If a value for `max-depth` is not specified, there is no limit on the depth of the file hierarchy for this request.

Example

If items 'B' to 'K' establish the contents of metadata-bin #3 as in the example for C.5.2.1, the `root-bin` field is set to 3 and `max-depth` is set to 0, then the request is limited to items 'B' to 'D'. If `max-depth` is set to 1, the request is limited to items 'B' to 'G'.

The request `metareq=[roid]R3D0` would therefore not request any data from the server because the only ROI description box within the specified bin is one level below the start of bin #3. The request `metareq=[asoc]R3D0` would request the association box starting at label 'D' and its contents, items 'E' to 'K'. This request is identical to `metareq=[asoc]R3D3` because, even though the latter example also requests the association box starting at label 'G', this box is part of the box starting at label 'D' and is thus included in the former request anyhow.

C.5.2.4 I-box-prop

The `req-box-prop` portion of the request specifies a list of box types that are of interest to the client. The special string "*" may be substituted for the box type, in which case all box types are implied. Thus, this field confines the request to apply only to the specific box type (or types) listed and instructs the server to deliver the box header and box contents of all matching boxes within all additional constraints.

The contents of a superbox is defined by its complete sub-box hierarchy. This implies that in case superboxes match the box type, the complete sub-box hierarchy of the matching superbox is requested, regardless of the `max-depth` field.

Example

Consider again the example layout of C.5.2. Then, a `req-box-prop` of type `'asoc'` would include all items 'A' to 'K' in the request because they establish the content of the matching box defined at label 'A'. Note that, once the association box at label 'A' has been identified to match the request, the depth limit does not limit the delivery of its contents. A `req-box-prop` of type `'1b1\040'` would only include items 'H' and 'I', along with all other label boxes, provided they match all other specifications of the request, e.g., are contained in the addressed root bin above the depth-limit.

The request `metareq=[*]R3D0` instructs the server to return the entire contents of all boxes it finds in the contents of bin 3, and thus requests items 'B' to 'K'. While a restriction on the desired depth has been specified, the server shall ignore that restriction because items 'E' to 'K' are part of the box starting at label 'D' and no other constraints apply.

C.5.2.5 limit

The `limit` attribute optionally following the `req-box-prop` field further confines the type of request, and how many bytes of the box contents identified by the `req-box-prop` field the client is interested in. The `limit` parameter takes the form of a colon followed by either an unsigned integer (the limit value) or the character "r". The same limit value applies to all boxes that match the `req-box-prop` of which it is an attribute. If it is not present, the client is requesting all matching boxes entirely.

If the `limit` field is an integer `n` greater than zero, then the server is requested to return the unlimited box header and only the first `n` bytes of the box content of the matching boxes. The byte count is here defined to count the data as it appeared in the original file before it was broken up into bins.

Furthermore, if `req-box-prop` matches any superboxes, the contents of a superbox is to be understood as the complete and unlimited sequence of box headers and box contents contained within that superbox, and the byte limit by that also counts the box headers of all boxes contained within the matching super box. It may thus happen that the `limit` field instructs the server to deliver only parts of a (sub-)box header even though the full header of the matching box itself is always included. However, using the `limit` field in this way is discouraged and should be avoided.

If the `limit` field is zero, only the box headers of the matching boxes are requested.

If the `limit` value is "r", then the server is requested to deliver the minimum data required to reconstruct the box-headers of all matching boxes, as well as the minimum data to reconstruct the box-headers of all of its descendant sub-boxes up to the maximum depth specified, regardless of their box-type. Note that, as an exception, `max-depth` does apply for the `limit` value "r" to limit the contents of superboxes, which makes this type of request special as far as the interpretation of `max-depth` is concerned.

Example

Consider again a file layout as in C.5.2 above with items 'B' to 'K' in data bin #3 and the metadata request `metareq=[asoc:8]R3D1`. By that, the client requires the box header and the first eight bytes of every association box found in bin #3 not deeper than one level from bin #3. In the example at hand, this requests the item 'D', eight bytes from item 'E', namely the part of the first sub-box of 'D' that fits into the limit because it establishes the contents of 'D', the item 'G' because it is exactly one level below the first item 'B' of the bin, and eight bytes of the box content contained in the superbox starting at 'G', that is the first eight bytes of the box header 'H'. Should the box headers 'E' and 'H' not fit into eight bytes, they might get truncated. This is why usage of the numerical limit field on superboxes is discouraged.

Consider the request `metareq=[roid:1]R3D1`. This will request the box header of the ROI description box at label 'E' one level below the start of the bin, and in addition the first byte of its contents at point 'F', which happens to be the number of regions encoded in the box (see Rec. ITU-T T.801 | ISO/IEC 15444-2). If the example would contain a ROI description box at a deeper level, it would not be requested here due to the depth limit.

The request `metareq=[asoc]R3D0` does not contain a limit, and thus requests the complete body of any association box found at the box level of metadata-bin #3. Even though the association box at label 'G' is outside the depth-limit, it is still requested because it is contained in the association box started at point 'D', and by that items 'D' to 'K' are transmitted completely.

The "r" limit is in effect a request for a skeleton of a portion of the box hierarchy because it only supplies the minimum data, namely the box headers, to reconstruct the structure of the boxes. The request `metareq=[asoc:r]R3D1` thus requests the items at label 'D', 'E' and 'G', but not 'H' and 'J' because they are outside the depth-limit. Item 'A' is not part of bin #3 in the example set-up, and is thus neither requested.

The difference between the limit "0" and the limit "r" is that the former only delivers the box header of all matching boxes, but not necessarily their depending sub-boxes. The "r" limit, however, extends the request to the box-headers of the sub-structure of the matching box up to the depth-limit.

C.5.2.6 metareq-qualifier

The "metareq-qualifier" takes the form of a "/" followed by one or more of the flags "g", "s", "w" and "a". Each flag identifies a context from which boxes which match the request shall be drawn. Thus, the "metareq-qualifier" defines an additional constraint on the boxes besides the box-type. The interpretation for each of these contexts is supplied in Table C.2. If more than one of the flags is provided, the union of the corresponding contexts shall be taken.

The contexts "g", "s" and "w" are mutually exclusive, but their union is generally smaller than the catch-call context "a". It is at the discretion of the server to decide which box falls into which context, and no classification of box types is defined in this Recommendation | International Standard.

C.5.2.7 priority

If the "priority" flag is specified, then the client is requesting that the data collected by the meta-data request has to be transmitted with higher priority (i.e., upfront) than the image data described by other fields of the same request.

C.5.2.8 metadata-only

If "metadata-only" is specified at the end of the meta-data request field, the client is requesting that the server's response consists only of meta-data, without any image data or codestream headers, regardless of whether view-window request fields such as Frame Size have been used. For JPP-stream and JPT-stream return types, this means that the returned JPIP messages will all be metadata-bin messages. This field also disables the request of the silently implied meta-data defined by C.5.1.

C.5.2.9 Implications of layout-constraints

Regardless of the box specifications provided via the Metadata Request field, the server may send other data, either because it has determined that the other data is required for the client to decode or interpret the requested image data, or because the server had previously divided the logical target into data-bins using different criteria, and additional data shall be sent in order to provide a consistent and meaningful view of the metadata-bins for this logical target.

To make the delivered data parseable to a client, all data from the start of the bin up to the last byte required to satisfy the request has to be known by the client, and thus has to be transmitted provided it is not already within the cache of the client. In addition, should any data that matches the request be relocated into additional bins by means of placeholder boxes, the complete placeholder box and the bytes of the bin referenced by the placeholder box has to be included in the request. Byte counts, as used by the limit attribute, always count bytes **as found in the original stream** and not as it was broken up by the server. This means that the number of bytes actually being transmitted back to the client might be different from the number of bytes implied by the byte-limit, because not only placeholder boxes have to be transmitted, but also the data in front of the requested bytes within the bin the bytes are located in might have to be included to make the resulting stream parseable.

Regardless of the box specifications provided via the metareq request field, the server may send other data, either because it has determined that the other data is required for the client to decode.

Example

Consider again the data as found at the beginning of C.5.2 and assume the server decided to place all of the data into metadata-bin #3 without making use of any (additional) placeholder boxes. Also assume that the cache of the client is empty. Then the metadata-request `metareq=[xml\040:r]R3` is requesting only the box header of the XML box at label 'J'. However, since the bin is not broken up into more bins, all bytes in front of item 'J' are also required by the client to parse this data successfully and to identify the transmitted data as a box header, and thus the server is required to send all data from 'B' to 'J'.

As the above example suggests, not using placeholders might be considerably inefficient for some requests. The following alternative layout at the server side provides a more efficient access to the same data:

The association boxes at 'D' and 'G' are broken up into separate bins with the bin-ids #4 and #5, respectively. Then for the very same request, the server would have to transmit the placeholder box for item 'D' in bin #3, the placeholder box for item 'G' in bin #4 and the requested box header 'J' now located at the start of bin #5. Note that the request automatically pertains to bins #4 and #5, since they are referenced by placeholders in bins #3 and #4 respectively. Depending on the size of the remaining boxes, this layout might be considerably more efficient.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks
Series Z	Languages and general software aspects for telecommunication systems