



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

X.509

Corrigendum 3

(10/2001)

SERIES X: DATA NETWORKS AND OPEN SYSTEM
COMMUNICATIONS

Directory

Information technology – Open Systems
Interconnection – The Directory: Authentication
framework

Technical Corrigendum 3

ITU-T Recommendation X.509 (1997) – Corrigendum 3

(Formerly CCITT Recommendation)

ITU-T X-SERIES RECOMMENDATIONS
DATA NETWORKS AND OPEN SYSTEM COMMUNICATIONS

PUBLIC DATA NETWORKS	
Services and facilities	X.1–X.19
Interfaces	X.20–X.49
Transmission, signalling and switching	X.50–X.89
Network aspects	X.90–X.149
Maintenance	X.150–X.179
Administrative arrangements	X.180–X.199
OPEN SYSTEMS INTERCONNECTION	
Model and notation	X.200–X.209
Service definitions	X.210–X.219
Connection-mode protocol specifications	X.220–X.229
Connectionless-mode protocol specifications	X.230–X.239
PICS proformas	X.240–X.259
Protocol Identification	X.260–X.269
Security Protocols	X.270–X.279
Layer Managed Objects	X.280–X.289
Conformance testing	X.290–X.299
INTERWORKING BETWEEN NETWORKS	
General	X.300–X.349
Satellite data transmission systems	X.350–X.369
IP-based networks	X.370–X.399
MESSAGE HANDLING SYSTEMS	X.400–X.499
DIRECTORY	X.500–X.599
OSI NETWORKING AND SYSTEM ASPECTS	
Networking	X.600–X.629
Efficiency	X.630–X.639
Quality of service	X.640–X.649
Naming, Addressing and Registration	X.650–X.679
Abstract Syntax Notation One (ASN.1)	X.680–X.699
OSI MANAGEMENT	
Systems Management framework and architecture	X.700–X.709
Management Communication Service and Protocol	X.710–X.719
Structure of Management Information	X.720–X.729
Management functions and ODMA functions	X.730–X.799
SECURITY	X.800–X.849
OSI APPLICATIONS	
Commitment, Concurrency and Recovery	X.850–X.859
Transaction processing	X.860–X.879
Remote operations	X.880–X.899
OPEN DISTRIBUTED PROCESSING	X.900–X.999

For further details, please refer to the list of ITU-T Recommendations.

INTERNATIONAL STANDARD ISO/IEC 9594-8

ITU-T RECOMMENDATION X.509

**Information technology – Open Systems Interconnection – The Directory:
Authentication framework**

TECHNICAL CORRIGENDUM 3

Summary

This Technical Corrigendum covers resolutions to defect reports 272, 273, 275 and 277.

Source

Corrigendum 3 to ITU-T Recommendation X.509 (1997) was prepared by ITU-T Study Group 7 (2001-2004) and approved on 29 October 2001. An identical text is also published as Technical Corrigendum 3 to ISO/IEC 9594-8.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2002

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from ITU.

CONTENTS

	<i>Page</i>
1) This corrects the defects reported in defect report 272	1
2) This corrects the defects reported in defect report 273	1
3) This corrects the defects reported in defect report 275	4
4) This corrects the defects reported in defect report 277	4

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

**Information technology – Open Systems Interconnection – The Directory:
Authentication framework**

TECHNICAL CORRIGENDUM 3

(covering resolutions to defect reports 272, 273, 275 and 277)

1) This corrects the defects reported in defect report 272

*In 12.4.2.1, add the following text to the end of the paragraph that begins with "The **pathLenConstraint** component shall be present only if..."*

The constraint takes effect beginning with the next certificate in the path. The constraint restricts the length of the segment of the certification path between the certificate containing this extension and the end-entity certificate. It has no impact on the number of CA-certificates in the certification path between the trust anchor and the certificate containing this extension. Therefore, the length of a complete certification path may exceed the maximum length of the segment constrained by this extension. The constraint controls the number of non self-issued CA certificates between the CA certificate containing the constraint and the end-entity certificate. Therefore the total length of this segment of the path, excluding self-issued certificates, may exceed the value of the constraint by as many as two certificates. (This includes the certificates at the two endpoints of the segment plus the CA certificates between the two endpoints that are constrained by the value of this extension.)

2) This corrects the defects reported in defect report 273

Replace 12.4.2.2 with the following:

12.4.2.2 Name constraints extension

This field, which shall be used only in a CA-certificate, indicates a name space within which all subject names in subsequent certificates in a certification path must be located. This field is defined as follows:

```
nameConstraints EXTENSION ::= {
  SYNTAX          NameConstraintsSyntax
  IDENTIFIED BY   id-ce-nameConstraint }
```

```
NameConstraintsSyntax ::= SEQUENCE {
  permittedSubtrees      [0]  GeneralSubtrees OPTIONAL,
  excludedSubtrees      [1]  GeneralSubtrees OPTIONAL,
  requiredNameForms     [2]  NameForms OPTIONAL }
```

```
GeneralSubtrees ::= SEQUENCE SIZE (1..MAX) OF GeneralSubtree
```

```
GeneralSubtree ::= SEQUENCE {
  base          GeneralName,
  minimum      [0]  BaseDistance DEFAULT 0,
  maximum      [1]  BaseDistance OPTIONAL }
```

```
BaseDistance ::= INTEGER (0..MAX)
```

```
NameForms ::= SEQUENCE {
  basicNameForms  [0]  BasicNameForms OPTIONAL,
  otherNameForms  [1]  SEQUENCE SIZE (1..MAX) OF OBJECT IDENTIFIER OPTIONAL }
```

(ALL EXCEPT ({ -- none; i.e.:at least one component shall be present -- }))

```

BasicNameForms ::= BIT STRING {
    rfc822Name      (0),
    dnsName         (1),
    x400Address     (2),
    directoryName   (3),
    ediPartyName    (4),
    uniformResourceIdentifier (5),
    ipAddress       (6),
    registeredID    (7) } (SIZE (1..MAX))

```

If present, the **permittedSubtrees** and **excludedSubtrees** components each specify one or more naming subtrees, each defined by the name of the root of the subtree and optionally, within that subtree, an area that is bounded by upper and/or lower levels. If **permittedSubtrees** is present, subject names within these subtrees are acceptable. If **excludedSubtrees** is present, any certificate issued by the subject CA or subsequent CAs in the certification path that has a subject name within these subtrees is unacceptable. If both **permittedSubtrees** and **excludedSubtrees** are present and the name spaces overlap, the exclusion statement takes precedence for names within that overlap. If neither permitted nor excluded subtrees are specified for a name form, then any name within that name form is acceptable. If **requiredNameForms** is present, all subsequent certificates in the certification path must include a name of at least one of the required name forms.

If **permittedSubtrees** is present, the following applies to all subsequent certificates in the path. If any certificate contains a subject name (in the **subject** field or **subjectAltNames** extension) of a name form for which permitted subtrees are specified, the name must fall within at least one of the specified subtrees. If any certificate contains only subject names of name forms other than those for which permitted subtrees are specified, the subject names are not required to fall within any of the specified subtrees. For example, assume that two permitted subtrees are specified, one for the DN name form and one for the rfc822 name form, no excluded subtrees are specified, but **requiredNameForms** is specified with the **directoryName** bit and **rfc822Name** bit present. A certificate that contained only names other than a directory name or rfc822 name would be unacceptable. If **requiredNameForms** were not specified, however, such a certificate would be acceptable. For example, assume that two permitted subtrees are specified, one for the DN name form and one for the rfc822 name form, no excluded subtrees are specified, and **requiredNameForms** is not present. A certificate that only contained a DN and where the DN is within the specified permitted subtree would be acceptable. A certificate that contained both a DN and an rfc822 name and where only one of them is within its specified permitted subtree would be unacceptable. A certificate that contained only names other than a DN or rfc822 name would also be acceptable.

If **excludedSubtrees** is present, any certificate issued by the subject CA or subsequent CAs in the certification path that has a subject name (in the **subject** field or **subjectAltNames** extension) within these subtrees is unacceptable. For example, assume that two excluded subtrees are specified, one for the DN name form and one for the rfc822 name form. A certificate that only contained a DN and where the DN is within the specified excluded subtree would be unacceptable. A certificate that contained both a DN and an rfc822 name and where at least one of them is within its specified excluded subtree would be unacceptable.

When a certificate subject has multiple names of the same name form (including, in the case of the **directoryName** name form, the name in the subject field of the certificate if non-null), then all such names shall be tested for consistency with a name constraint of that name form.

If **requiredNameForms** is present, all subsequent certificates in the certification path must include a subject name of at least one of the required name forms.

Of the name forms available through the **GeneralName** type, only those name forms that have a well-defined hierarchical structure may be used in the **permittedSubtrees** and **excludedSubtrees** fields. The **directoryName** name form satisfies this requirement; when using this name form a naming subtree corresponds to a DIT subtree.

The **minimum** field specifies the upper bound of the area within the subtree. All names whose final name component is above the level specified are not contained within the area. A value of **minimum** equal to zero (the default) corresponds to the base, i.e. the top node of the subtree. For example, if **minimum** is set to one, then the naming subtree excludes the base node but includes subordinate nodes.

The **maximum** field specifies the lower bound of the area within the subtree. All names whose last component is below the level specified are not contained within the area. A value of **maximum** of zero corresponds to the base, i.e. the top of the subtree. An absent **maximum** component indicates that no lower limit should be imposed on the area within the subtree. For example, if **maximum** is set to one, then the naming subtree excludes all nodes except the subtree base and its immediate subordinates.

This extension may, at the option of the certificate issuer, be either critical or non-critical. It is recommended that it be flagged critical, otherwise a certificate user may not check that subsequent certificates in a certification path are located in the name space intended by the issuing CA.

Conformant implementations are not required to recognize all possible name forms.

If the extension is present and is flagged critical, a certificate-using implementation must recognize and process all name forms for which there is both a subtree specification (permitted or excluded) in the extension and a corresponding value in the **subject** field or **subjectAltNames** extension of any subsequent certificate in the certification path. If an unrecognized name form appears in both a subtree specification and a subsequent certificate, that certificate shall be handled as if an unrecognized critical extension was encountered. If any subject name in the certificate falls within an excluded subtree, the certificate is unacceptable. If a subtree is specified for a name form that is not contained in any subsequent certificate, that subtree can be ignored. If the **requiredNameForms** component specifies only unrecognized name forms, that certificate shall be handled as if an unrecognized critical extension was encountered. Otherwise, at least one of the recognized name forms must appear in all subsequent certificates in the path.

If the extension is present and is flagged non-critical and a certificate-using implementation does not recognize a name form used in any **base** component, then that subtree specification may be ignored. If the extension is flagged non-critical and any of the name forms specified in the **requiredNameForms** component are not recognized by the certificate-using implementation, then the certificate shall be treated as if the **requiredNameForms** component was absent.

In 12.4.3, add a new path processing variable as follows and renumber subsequent bullets accordingly:

- d) *required-name-forms*: A (possibly empty) set of sets of name forms. For each set of name forms, every subsequent certificate must contain a name of one of the name forms in the set.

In 12.4.3, add a new initialization step as follows and renumber subsequent bullets accordingly:

- d) Initialize the *required-name-forms* to an empty set;

In 12.4.3, add a step to the checks applied to all certificates as follows:

- h) If the certificate is not an intermediate self-issued certificate, and if *required-name-forms* is not an empty set, for each set of name forms in *required-name-forms* check that there is a subject name in the certificate of one of the name forms in the set.

In 12.4.3, add a step to the constraint recording actions applied to intermediate certificates as follows:

- c) If the **nameConstraints** extension with a **requiredNameForms** component is present in the certificate, set the *required-name-forms* variable to the union of its previous value and the set consisting of the set of name forms specified in the certificate extension. If the **requiredNameForms** component contains more than one name form, the *required-name-forms* variable shall signal that a name of at least one of the indicated name forms in this extension shall be present in all subsequent certificates. The union of a previous value of the *required-name-forms* variable with the value from the current certificate extension is a set of sets signalling requirements for all subsequent certificates. For example if the current *required-name-forms* is set to requiring that either a DN or an rfc822 name must be present in certificates and the current extension in the certificate being processed indicates that either rfc822 names or DNS names are required, the resulting union that is the new *required-name-forms* indicates that each of the subsequent certificates must have either an rfc822 name or both a DN and a DNS name.

In Annex A, certificateExtensions module update the ASN.1 for nameConstraints extension as above.

In Annex A, certificateExtensions module add the following:

id-ce-nameConstraint OBJECT IDENTIFIER ::= {id-ce 30 1}

In Annex A, certificateExtensions module, delete the following:

id-ce-nameConstraints OBJECT IDENTIFIER ::= {id-ce 30}

In Annex A, certificateExtensions module, add the following to the set of OIDs not used in this Specification:

id-ce 30

3) This corrects the defects reported in defect report 275

*In 12.2.2.4, add the following as a new second paragraph following the ASN.1 for the **extKeyUsage** extension.*

A CA may assert any-extended-key-usage by using the **anyExtendedKeyUsage** identifier. This enables a CA to issue a certificate that contains OIDs for extended key usages that may be required by certificate-using applications, without restricting the certificate to only those key usages. If extended key usage would restrict key usage, then the inclusion of this OID removes that restriction.

anyExtendedKeyUsage OBJECT IDENTIFIER ::= { 2 5 29 37 0 }

4) This corrects the defects reported in defect report 277

In 12.4.2.3, in the last sentence of the second paragraph:

Replace "which is the subject of a subsequent certificate" with "which is the issuer of a subsequent certificate".

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure and Internet protocol aspects
Series Z	Languages and general software aspects for telecommunication systems